



# SPECIFICATION SHEET

## 43-859



### KUT GARD® KEVLAR® / PREOX SEAMLESS KNIT HOT MILL GLOVE WITH COTTON LINER AND DOUBLE-SIDED SILAGRIP™ COATING - EXTENDED CUFF

- Seamless construction offers increased comfort and breathability
- Kevlar®/Preox blend shell provides excellent cut, abrasion and thermal protection as well as inherently flame resistant
- 100% terry cotton lined for extra comfort
- Double-sided SilaGrip™ coating resists melting in very hot applications
- Ambidextrous pattern permits glove to be worn on either hand, extending wear and reducing costs
- Extended open cuff allows for easy on/off and arm protection
- Meets OSHA CFR 1910.269 standards
- Torch Testing: Our Preox outer shell evenly disburses the heat energy and will take about 60 seconds before the heat will start penetrating the next layer of fabric. Preox will not ignite or burn even when exposed to temperatures exceeding 1600°F for over 120 seconds.
- Protects against the intense heat of an electric arc complying with NFPA 70E standards

#### APPLICATIONS

- Hot metal handling
- Glass handling
- Foundries
- Forging operations

#### CARE INSTRUCTIONS

Machine wash in warm water (120°F max) with detergent rinse thoroughly, and tumble dry on low heat. Do not use fabric softeners or bleach. Can be dry cleaned for greater longevity.

#### TECHNICAL DATA

MATERIAL	Cotton, Preox / Kevlar®
CONSTRUCTION	<i>Outer shell:</i> pre-oxidized, thermally stabilized polyacrylonitrile and Para-aramid <i>Lining:</i> 100% cotton terry
COLOR	■ Dark Green
CUFF STYLE	Extended cuff
SIZES	Men's
PACKAGING	12 per dozen, 2 dozen per case
CASE DIMENSIONS	12" x 12" x 12" / 30.5cm x 30.5cm x 30.5cm
CASE WEIGHT	12.4 lbs / 5.6 kgs
COO	USA

#### CUT RESISTANCE PROPERTIES

- ASTM F2992-15 ANSI Cut Level A4 (Adopted by ANSI/ISEA 02/16)
- ASTM F1790-05 ANSI Cut Level 4

#### BARCODES

ITEM	DOZEN	CASE
■ 43-859	01616314055965	02616314055964



#### DIMENSIONS (in/cm)

	MEN'S	---
<b>A</b>	17 / 43.2	---
<b>B</b>	5.0 / 12.7	---

