



# SPECIFICATION SHEET

## 44-6745



### MAXICUT® ULTRA™ BY ATG®, DYNEEMA® DIAMOND BLENDED SHELL, BLACK MICRO-FOAM NITRILE COATING

- Micro-Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Dyneema® Diamond blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Reinforcement between the thumb and forefinger
- Patented micro-foam nitrile coating offers 360° breathability making it the most breathable cut resistant glove on the market
- Optimized grip delivered through our micro-cup finish
- Minimal penetration (strike through) leaving only the soft liner resting against the skin
- The Skin Health Alliance has awarded professional dermatological accreditation following review of the scientific dossier behind this product

#### APPLICATIONS

- DIY and Gardening
- Finishing and inspection
- Handling of small components
- Primary, secondary and final assembly
- Maintenance
- Logistics and warehousing
- Using tools and instruments

#### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

#### TECHNICAL DATA

MATERIAL	Dyneema® Diamond, Nylon, Spandex				
COLOR	Light Blue/Black				
CUFF STYLE	Continuous Knit				
SIZES	S - XXL				
PACKAGING	12 per dozen, 6 dozen per case				
CASE	19.7" x 11.6" x 7.9" / 50cm x 29.5cm x 20cm				
CASE WEIGHT	S	M	L	XL	XXL
	9.9 lbs 4.5 kg	10.5 lbs 4.75 kg	11 lbs 5 kg	11.9 lbs 5.4 kg	12.5 lbs 5.65 kg
COO	Sri Lanka				

#### PERFORMANCE PROPERTIES

EN388: 4X43C	ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16)					
	ASTM F1790-05 ANSI Cut Level 3					
ABRASION	0	1	2	3	4	5
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT (TDM-100)	A	B	C	D	E	F




#### BARCODES

ITEM	PAIR	DOZEN	CASE
44-6745/S	616314250507	01616314250506	02616314250505
44-6745/M	616314250514	01616314250513	02616314250512
44-6745/L	616314250521	01616314250520	02616314250529
44-6745/XL	616314250538	01616314250537	02616314250536
44-6745/XXL	616314250545	01616314250544	02616314250543

#### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
A	8.27 / 21	8.66 / 22	9.6 / 23	9 / 23	9.3 / 23.5
B	3.4 / 8.7	3.5 / 9	3.7 / 9.4	3.8 / 9.6	3.9 / 9.8
H	Red	Orange	White	Yellow	Black



#### PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.