



Capacitive Sensors

Series 80 - PNP

Housing $\varnothing = 26 \text{ mm}$ / F30


- Housing material PTFE
- SIP / CIP 121° C
- Useable for an ambient temperature up to +100 °C
- Ideal of detection of chemically aggressive media
- Suitable for foods and pharmaceutical applications
- Special version with flange, double gasket for hole basis fitting $\varnothing 30 \text{ mm}$

Certificate:



Technical data	Non-flush mountable
Operating distance S_n	5 mm
Operating distance min./max. adjustable	0...20 mm
Electrical version	4-pin DC
Output	Antivalent (NO + NC)
Type NPN	
Art.-No.	
Connection diagram No..	
Type PNP	KAS-80-26/F30-A-PTFE-100°C-Y5
Art.-No.	KA 0626
Connection diagram No.	6
Operating voltage (U_B)	10...35 V DC
Output current max. (I_o)	2 x 250 mA
Load current min.	-
Voltage drop max. (U_d)	$\leq 2.0 \text{ V}$
Permitted residual ripple max.	10%
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+100° C / CIP 121° C (zero-current)
LED-display	Green/yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1
Housing material	PTFE
Active surface	PTFE
Lid	PA

All specifications are subject to change without notice. (27.03.2008)



Made in Germany