

## Spring Retractable Fuel Hose Reels



3/4", 1", 1 1/2" I.D.

- Ideal for mobile and permanent-mount applications
- Suitable for a wide variety of fuel applications including E85
- Incorporates metal forms to ensure the greatest possible strength
- Latch and ratchet are made of heavy duty cast aluminum to limit the opportunity for premature wear
- Equipped with FKM seals
- Reels are all supplied with our ball-bearing style swivel



FHD79035 OLP

Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in		
<b>Low Pressure Fuel Reels</b> Maximum Temperature 150 °F (65 °C)															
<b>F7925 OLP</b> ★	47	21	3/4	19	1.188	30	25	8	*50	3	3/4	3/4	3/4	12	---
<b>FHD79035 OLP</b>	79	36	3/4	19	1.188	30	35	11	*50	3	3/4	3/4	3/4	13	2
<b>F83050 OLP</b>	89	40	3/4	19	1.188	30	50	15	*50	3	3/4	3/4	3/4	14	1
<b>FD83075 OLP</b>	115	52	3/4	19	1.188	30	75	23	*50	3	3/4	3/4	3/4	14	2
<b>FD84035 OLP</b>	94	43	1	25	1.500	38	35	11	*50	3	1	1	1	14	3
<b>FD84050 OLP</b> ★	115	52	1	25	1.500	38	50	15	*50	3	1	1	1	14	3
<b>FSD14050 OLP</b>	127	58	1	25	1.500	38	50	15	*50	3	1	1	1	refer to reelcraft.com	
<b>FE9450 OLPBW</b>	157	71	1	25	1.500	38	50	15	*50	3	1	1	1	16	1

\*Models supplied with UL330 and cUL Nitrile synthetic rubber (ORS) hose. 250 psi minimum burst (17 Bar). Flow rates of fuel hose are reduced by 30% with addition of internal spring type bend restrictors. For example, flow rate of F7925 OLP with internal bend restrictors is 9.0 GPM at 40 psi; flow without internal bend restrictors is 13.0 GPM at 40 psi.

Model without hose & bumper	Shipping Weight		Hose Capacity			Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet	Size Index Page	Size Index #				
	lbs	kg	I.D.	O.D.	Length									
<b>Low Pressure Fuel Reels</b> Maximum Temperature 210 °F (99 °C)														
<b>F7900 OLP</b>	45	20	3/4	19	1.188	30	25	8	500	35	3/4	3/4	12	---
<b>F83000 OLP</b>	74	34	3/4	19	1.188	30	50	15	500	35	3/4	3/4	14	1
<b>FD83000 OLP</b>	82	37	3/4	19	1.188	30	75	23	500	35	3/4	3/4	14	2
<b>FD84000 OLP</b>	84	38	1	25	1.500	38	50	15	500	35	1	1	14	3
<b>FE9400 OLPBW</b>	115	52	1	25	1.500	38	50	15	500	35	1	1	16	1
<b>FF9600 OLPBW</b> ★	135	61	1 1/2	38	2.000	51	50	15	600	41	1 1/2	1 1/2	16	5

Hose Assemblies	Hose I.D.		Hose O.D.		Hose Length		Max Pressure		End Fittings	Shipping Weight	
	in	mm	in	mm	ft	m	psi	bar	in - NPT(M)	lbs	kg
<b>Low Pressure Fuel Inlet Hose</b> 4 spiral poly yarn braid											
<b>S600451-2</b>	1	25	1.500	38	2	0.6	50	3	1 x 1	1.7	0.8
<b>Low Pressure Fuel Outlet Hoses</b> 4 spiral poly yarn braid											
<b>S600160-1</b>	3/4	19	1.188	30	25	8	50	3	3/4 x 3/4	17.5	7.9
<b>S600160-4</b>	3/4	19	1.188	30	35	11	50	3	3/4 x 3/4	24.5	11.1
<b>S600160-2</b>	3/4	19	1.188	30	50	15	50	3	3/4 x 3/4	35.0	15.9
<b>S600160-3</b>	3/4	19	1.188	30	75	23	50	3	3/4 x 3/4	52.5	23.8
<b>S600451-35</b>	1	25	1.500	38	35	11	50	3	1 x 1	30.0	13.6
<b>S600451-50</b>	1	25	1.500	38	50	15	50	3	1 x 1	42.0	19.1

**Caution:** Be sure working pressure required does not exceed above ratings. Misapplication can result in serious operator injury.



S600451-35



S600160-2

**NEW!**  
**Reel Covers**  
See page 36

**Interactive Reel Catalog**  
Visit [reelcraft.com/catalog](http://reelcraft.com/catalog) for complete product specifications, parts, and accessories.

Models with a ★ icon are our most popular models.

**Pivot Bases & Swing Brackets**  
See page 39