Air Vend Hose Reels Series AV


The Series AV from Reelcraft is designed for air service. The air vend reels are compact and able to handle 25' of 1/4" hose. It is small enough to be incorporated into air service stations or inside cabinets on trucks. Reels are supplied with a tougher one wire braid hose to resist abrasion and crushing.

Benefits


- **Durable** Reel is made from heavy gauge industrial steel and hose is abrasion/crush resistant one wire braid.
- **Corrosion resistant** Components are individually powder coated prior to assembly for a nearly impervious uniform finish.
- **Ease of use** External guard eliminates the possibility of hose "jumping" off the spool during rewind (AV4425 models only).
- **Serviceable** External swivel design offers easy access to serviceable parts (AV4425 models only).
- Extra protection Feature a steel enclosure that offers an additional level of protection for the hose from potentially harmful foreign debris. Reel is designed such that removing the cover on either side will allow access to the majority of serviceable parts (AV5425 ELP).

Related Products

Reelcraft offers a complete line of over 2,500 hose, cord and cable reels. For a complete product listing visit us online at www.reelcraft.com or call toll free 800-444-3134.









AV5425 ELP

AV4425 OLPBWR

Accessories

Accessory	Description	Weight			
		lbs	kg		
602366	Series 4000 jump guard	3	1.36		
HR1145	Cabinet roller guide	0.5	0.23		

Model with hose	Shipping Weight Pressure		Hose I.D.		Hose O.D.		NPT(M) Outlet		Hose Length		Inlet Connection			
with nose	lbs	kg	psi	bar	in	mm	in mn	n	in	in	ft	m	Location	
Low Pressure Reels Maximum Temperature 150 °F (65 °C)														
AV4425 OLPBWL	18	8	300	21	1/4	6	.470 1	2	1/4	3/8	25	8	Swivel Side	
AV4425 OLPBWR	18	8	300	21	1/4	6	.470 1	2	1/4	3/8	25	8	Spring Case Side	
AV5425 ELP	35	16	300	21	1/4	6	.470 1	2	1/4	3/8	25	8	Spring Case Side	

Customer Service: 1.855.634.9109 All Other Calls: 1.800.444.3134

www.reelcraft.com reelcraft@reelcraft.com

