

# Compact, Versatile Reels | Series 4000 / 5000 / 5005

Made in USA 



4625 OLP


5635 OLP

5650 OLP

## Premium Duty Spring Retractable Reels

**Air/Water/Oil/Grease** - 1/4", 3/8", 1/2" I.D.

Series 4000, 5000, and 5005 reels are all-steel construction and compact for a wide range of applications with critical space requirements. A full flow shaft and swivel assures maximum product delivery. Guide arm adjusts to two positions.

	Dimensions - Size Index							
	1		2		3		4	
	in	mm	in	mm	in	mm	in	mm
<b>A</b>	12 <sup>7</sup> / <sub>8</sub>	327	14 <sup>3</sup> / <sub>8</sub>	365	17 <sup>5</sup> / <sub>8</sub>	448	17 <sup>5</sup> / <sub>8</sub>	448
<b>B</b>	12 <sup>5</sup> / <sub>8</sub>	321	14 <sup>1</sup> / <sub>4</sub>	362	16 <sup>3</sup> / <sub>4</sub>	425	16 <sup>3</sup> / <sub>4</sub>	425
<b>C</b>	8	203	9 <sup>3</sup> / <sub>4</sub>	248	9 <sup>3</sup> / <sub>4</sub>	248	9 <sup>3</sup> / <sub>4</sub>	248
<b>D</b>	2 <sup>1</sup> / <sub>2</sub>	64	2 <sup>1</sup> / <sub>2</sub>	64	2 <sup>1</sup> / <sub>2</sub>	64	2 <sup>1</sup> / <sub>2</sub>	64
<b>E</b>	5 <sup>5</sup> / <sub>8</sub>	143	6 <sup>1</sup> / <sub>8</sub>	156	5 <sup>7</sup> / <sub>8</sub>	149	7 <sup>1</sup> / <sub>4</sub>	184

**NOTE:** See operating instructions for optimum mounting configuration.



### Air Vend Reels


AV4425 OLPBWR

Visit [www.reelcraft.com/catalog](http://www.reelcraft.com/catalog) for air vend reels.

### Side Mount Reels

4625 OLP SML

Visit [www.reelcraft.com/catalog](http://www.reelcraft.com/catalog) for side mount models.



Quiet latch with Hose	Ratchet latch with Hose	Shipping Weight	Hose I.D.	Hose O.D.	Hose Length	**Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	Quiet latch without hose or bumper	Shipping Weight	Pressure	Size Index #
lbs kg	in mm	in mm	ft m	psi bar	in	in	lbs kg	psi bar		lbs kg	psi bar	
<b>Low Pressure Air/Water Reels</b> Maximum temperature 150 °F (65 °C) w/hose / 210 °F (99 °C) w/o hose **Maximum working pressure at 70 °F (20 °C)												
4420 OLP	-----	18 8	1/4 6	.475 12	20 6	300 21	1/4	3/8	<b>4400 OLP</b>	17 8	500 35	1
4425 OLP	<b>B4425 OLP</b>	19 9	1/4 6	.475 12	25 8	300 21	1/4	3/8	<b>4400 OLP</b>	17 8	500 35	1
4435 OLP	<b>B4435 OLP</b>	19 9	1/4 6	.475 12	35 11	300 21	1/4	3/8	<b>4400 OLP</b>	17 8	500 35	1
5450 OLP	<b>B5450 OLP</b>	26 12	1/4 6	.475 12	50 15	300 21	1/4	3/8	<b>5400 OLP</b>	20 9	500 35	2
4617 OLP	-----	19 9	3/8 10	.600 15	17 5	300 21	1/4	3/8	<b>4600 OLP</b>	17 8	500 35	1
4625 OLP	<b>B4625 OLP</b>	20 9	3/8 10	.600 15	25 8	300 21	1/4	3/8	<b>4600 OLP</b>	17 8	500 35	1
5635 OLP	<b>B5635 OLP</b>	25 11	3/8 10	.600 15	35 11	300 21	1/4	3/8	<b>5600 OLP</b>	21 10	500 35	2
5650 OLP	<b>B5650 OLP</b>	36 16	3/8 10	.600 15	50 15	300 21	1/4	3/8	<b>5605 OLP</b>	31 14	500 35	3
<b>A5825 OLP</b>	<b>B5825 OLP</b>	27 12	1/2 13	.750 19	25 8	300 21	1/2	3/8	<b>A5800 OLP</b>	22 10	500 35	2
<b>A5835 OLP</b>	<b>B5835 OLP</b>	39 18	1/2 13	.750 19	35 11	300 21	1/2	3/8	<b>A5805 OLP</b>	32 15	500 35	3
<b>A5850 OLP</b>	<b>B5850 OLP</b>	41 19	1/2 13	.750 19	50 15	300 21	1/2	3/8	<b>A5806 OLP</b>	35 16	500 35	4
<b>Medium Pressure Oil Reels</b> Maximum temperature 210 °F (99 °C)												
<b>5435 OMP</b>	<b>B5435 OMP</b>	31 14	1/4 6	.530 13	35 11	2750 190	1/4	3/8	<b>5400 OMP</b>	23 10	3000 207	2
<b>5630 OMP</b>	<b>B5630 OMP</b>	31 14	3/8 10	.690 18	30 9	2600 179	3/8	3/8	<b>5600 OMP</b>	24 11	3000 207	2
<b>A5825 OMP*</b>	<b>B5825 OMP*</b>	34 15	1/2 13	.820 21	25 8	3000 207	1/2	3/8	<b>A5800 OMP</b>	24 11	3000 207	2
<b>A5835 OMP</b>	<b>B5835 OMP</b>	42 19	1/2 13	.820 21	35 11	3000 207	1/2	3/8	<b>A5805 OMP</b>	32 15	3000 207	3
<b>High Pressure Grease Reels</b> Maximum temperature 210 °F (99 °C)												
<b>5430 OHP</b>	-----	30 14	1/4 6	.580 15	30 9	5000 345	1/4	1/4	<b>5400 OHP</b>	23 10	5000 345	2
<b>5435 OHP</b>	<b>B5435 OHP</b>	39 18	1/4 6	.580 15	35 11	5000 345	1/4	1/4	<b>5405 OHP</b>	33 15	5000 345	3
<b>5625 OHP</b>	<b>B5625 OHP</b>	32 15	3/8 10	.730 19	25 8	4800 331	1/4	1/4	<b>5600 OHP</b>	26 12	5000 345	2

\*Floor tank mount only - do not mount on ceiling. Low pressure reels furnished standard with PVC hose. Compressed air hoses should not be converted to oxygen service - may cause explosion when O<sub>2</sub> mixes with fuel. Medium pressure reels furnished standard with S.A.E. 100R1-AT (1/4" and 3/8") or S.A.E. 100R17 (1/2") one wire braid hose. High pressure reels furnished standard with S.A.E. 100 R2T two wire braid hose. Reference page 6 for guide arm positions.

**Prop 65:**  **WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Interactive Reel Catalog

Visit [www.reelcraft.com/catalog](http://www.reelcraft.com/catalog) for complete product specifications, available parts and accessories.



Visit [reelcraft.com/quick-ship](http://reelcraft.com/quick-ship) for a complete list of Quick Ship Reels - models that can be shipped same day when the order is received by 1:00 PM Eastern Time for quantities of 10 or fewer.