

Inlet Hose Assemblies

Partial List - Refer to Reelcraft.com for a complete list

A flexible hose connection must be used between the hose reel inlet and the source of supply to prevent possible misalignment and binding or warranty is void. Please furnish the following information when ordering: part number, product, and pressure to be handled. **NOTE:** Swivel fittings are recommended to protect hose during installation.

| Part Number | I.D. in | O.D. in | Length ft | Pressure psi | End Fittings in - NPT(M) | Wgt. lbs |
|--|------------|------------|--------------|-----------------|-----------------------------|-------------|
| Low Pressure Air/Water Inlet Hoses - PVC nylon braid. Max temp 150°F (65°C) | | | | | | |
| S601024-2 | 3/8 | 0.600 | 2 | 300 | 3/8 x 3/8 | 0.9 |
| S601024-4 | 3/8 | 0.600 | 4 | 300 | 3/8 x 3/8 | 1.1 |
| S601024-6 | 3/8 | 0.600 | 6 | 300 | 3/8 x 3/8 | 2.7 |
| S601020-2 | 1/2 | 0.750 | 2 | 300 | 1/2 x 1/2 | 1.2 |
| S601020-4 | 1/2 | 0.750 | 4 | 300 | 1/2 x 1/2 | 1.6 |
| S601020-8 | 1/2 | 0.750 | 8 | 300 | 1/2 x 1/2 | 3.5 |
| S601026-2 | 3/4 | 1.075 | 2 | 250 | 3/4 x 3/4 | 1.4 |
| S601026-7 | 3/4 | 1.075 | 7 | 250 | 3/4 x 3/4 | 3 |
| S601026-10 | 3/4 | 1.075 | 10 | 250 | 3/4 x 3/4 | 4 |
| S601027-2 | 1 | 1.375 | 2 | 250 | 3/4 x 1 | 1.72 |
| S601027-5 | 1 | 1.375 | 5 | 250 | 1 x 1 | 3.25 |
| S600982-10 | 1 | 1.375 | 10 | 300 | 1 x 1 NPSH(F) | 4.2 |
| Swivel End Fitting - One End | | | | | | |
| S601034-3 | 3/4 | 1.075 | 3 | 300 | 3/4 x 3/4 | 2 |
| S601034-4 | 3/4 | 1.075 | 4 | 300 | 3/4 x 3/4 | 2.3 |
| S601034-5 | 3/4 | 1.075 | 5 | 250 | 3/4 x 3/4 | 4 |
| S601034-10 | 3/4 | 1.075 | 10 | 250 | 3/4 x 3/4 | 5 |
| S601027-4 | 1 | 1.375 | 4 | 250 | 1 x 1 | 3.3 |
| Swivel End Fitting - Both Ends | | | | | | |
| S601034-2 | 3/4 | 1.075 | 2 | 300 | 3/4 x 3/4 | 1.7 |
| S601026-5 | 3/4 | 1.075 | 5 | 250 | 3/4 x 3/4 | 2.6 |
| S601034-7 | 3/4 | 1.075 | 7 | 250 | 3/4 x 3/4 | 4 |
| Medium Pressure Oil Inlet Hoses 100 R1T one wire braid. Max temp 210°F (99°C) | | | | | | |
| S32-260043 | 3/8 | 0.710 | 2 | 2250 | 3/8 x 3/8 | 1 |
| S17-260043 | 1/2 | 0.850 | 2 | 3000 | 1/2 x 1/2 | 1.7 |
| S39-260043 | 1/2 | 0.850 | 5 | 2000 | 1/2 x 1/2 | 3 |
| High Pressure Grease Inlet Hoses 100 R2T two wire braid. Max temp 210°F (99°C) | | | | | | |
| S17-260044 | 1/4 | 0.58 | 2 | 5000 | 1/4 x 1/4 | 0.75 |
| S14-260044 | 3/8 | 0.73 | 2 | 4000 | 3/8 x 1/2 | 0.83 |
| Water Inlet Hoses PVC nylon braid with garden hose thread | | | | | | |
| S601025-4 | 1/2 | 0.750 | 4 | 300 | 1/2 x 3/4 | 1.5 |
| S601025-6 | 1/2 | 0.750 | 6 | 300 | 1/2 x 3/4 | 2 |

Replacement Outlet Hose Assemblies

Partial List - Refer to Reelcraft.com for a complete list

| Part Number | I.D. in | O.D. in | Length ft | Pressure psi | End Fittings in - NPT(M) | Wgt. lbs |
|--|------------|------------|--------------|-----------------|-----------------------------|-------------|
| Low Pressure Air/Water Hoses PVC nylon braid. Max temp 150°F (65°C) | | | | | | |
| S601001-25 | 1/4 | 0.475 | 25 | 300 | 1/4 x 1/4 | 3 |
| S601001-50 | 1/4 | 0.475 | 50 | 300 | 1/4 x 1/4 | 5 |
| S601013-25 | 3/8 | 0.600 | 25 | 300 | 1/4 x 1/4 | 4.5 |
| S601013-50 | 3/8 | 0.600 | 50 | 300 | 1/4 x 1/4 | 6 |
| S601012-50 | 3/8 | 0.600 | 50 | 300 | 1/4 x 3/8 | 6 |
| S601017-50 | 3/8 | 0.600 | 50 | 300 | 1/4 x 1/2 | 6 |
| S601017-70 | 3/8 | 0.600 | 75 | 300 | 1/4 x 1/2 | 7.9 |
| S601015-50 | 3/8 | 0.600 | 50 | 300 | 3/8 x 1/2 | 6.5 |
| S601015-75 | 3/8 | 0.600 | 75 | 300 | 3/8 x 1/2 | 8 |
| S601015-100 | 3/8 | 0.600 | 100 | 300 | 3/8 x 1/2 | 14 |
| S601020-25 | 1/2 | 0.750 | 25 | 300 | 1/2 x 1/2 | 5 |
| S601021-50 | 1/2 | 0.750 | 50 | 300 | 3/8 x 1/2 | 8 |
| S601022-50 | 1/2 | 0.750 | 50 | 300 | 1/2 x 1/2 | 9.5 |
| S601022-100 | 1/2 | 0.750 | 100 | 300 | 1/2 x 1/2 | 16 |
| S601026-25 | 3/4 | 1.075 | 25 | 250 | 3/4 x 3/4 | 7.7 |
| S601026-50 | 3/4 | 1.075 | 50 | 250 | 3/4 x 3/4 | 15 |
| S601026-75 | 3/4 | 1.075 | 75 | 250 | 3/4 x 3/4 | 18.75 |
| S601026-100 | 3/4 | 1.075 | 100 | 250 | 3/4 x 3/4 | 22.6 |
| S601027-50 | 1 | 1.375 | 50 | 250 | 3/4 x 1 | 21.8 |
| S601027-100 | 1 | 1.375 | 100 | 250 | 3/4 x 1 | 45 |
| S601027-100 | 1 | 1.375 | 100 | 250 | 3/4 x 1 | 45 |
| S601027-2 | 1 | 1.375 | 2 | 250 | 3/4 x 1 | 1.72 |
| S601027-5 | 1 | 1.375 | 5 | 250 | 1 x 1 | 3.25 |
| S600982-10 | 1 | 1.375 | 10 | 300 | 1 x 1 NPSH(F) | 4.2 |
| Swivel End Fitting - One End | | | | | | |
| S601035-75 | 1/2 | 0.750 | 75 | 300 | 1/2 x 1/2 | 20 |
| S601035-100 | 1/2 | 0.750 | 100 | 300 | 1/2 x 1/2 | 26.4 |
| S601035-200 | 1/2 | 0.750 | 200 | 300 | 1/2 x 1/2 | 53 |
| S601034-25 | 3/4 | 1.075 | 25 | 250 | 3/4 x 3/4 | 8 |
| S601034-50 | 3/4 | 1.075 | 50 | 250 | 3/4 x 3/4 | 15 |
| S601034-75 | 3/4 | 1.075 | 75 | 250 | 3/4 x 3/4 | 23 |
| S601034-100 | 3/4 | 1.075 | 100 | 250 | 3/4 x 3/4 | 31 |
| Medium Pressure Oil Hoses 100 R1T one wire braid. Max temp 210°F (99°C) | | | | | | |
| S43-260043 | 1/4 | 0.530 | 50 | 2750 | 1/4 x 1/4 | 7.9 |
| S12-260043 | 3/8 | 0.710 | 25 | 2250 | 3/8 x 3/8 | 6 |
| S46-260043 | 3/8 | 0.710 | 50 | 2250 | 3/8 x 3/8 | 10.2 |
| S5-260043 | 3/8 | 0.710 | 50 | 2250 | 3/8 x 1/2 | 10.4 |
| S8-260043 | 1/2 | 0.850 | 50 | 3000 | 1/2 x 1/2 | 14.1 |
| S24-260043 | 1/2 | 0.850 | 75 | 3000 | 1/2 x 1/2 | 22 |
| S27-260043 | 3/4 | 1.120 | 50 | 1250 | 3/4 x 3/4 | 22.2 |
| S28-260043 | 3/4 | 1.120 | 75 | 1250 | 3/4 x 3/4 | 30 |
| S27-260043 | 3/4 | 1.120 | 50 | 1250 | 3/4 x 3/4 | 22.20 |
| S28-260043 | 3/4 | 1.120 | 75 | 1250 | 3/4 x 3/4 | 30.00 |
| High Pressure Grease Hoses 100 R2T 2 wire braid. Max temp 210°F (99°C) | | | | | | |
| S9-260044 | 1/4 | 0.580 | 50 | 5000 | 1/4 x 3/8 | 12.7 |
| S13-260044 | 3/8 | 0.730 | 25 | 4000 | 1/4 x 1/4 | 9.7 |
| S5-260044 | 3/8 | 0.730 | 50 | 4000 | 1/4 x 3/8 | 19.2 |
| S25-260044 | 3/8 | 0.730 | 25 | 4000 | 3/8 x 3/8 | 9.7 |
| S27-260044 | 3/8 | 0.730 | 50 | 4000 | 3/8 x 3/8 | 20.7 |
| S22-260044 | 3/8 | 0.730 | 100 | 4000 | 3/8 x 3/8 | 33 |
| S19-260044 | 3/8 | 0.730 | 50 | 4000 | 3/8 x 1/2 | 20.9 |
| S18-260044 | 3/8 | 0.730 | 75 | 4000 | 3/8 x 1/2 | 26.6 |
| S18-260044 | 3/8 | 0.730 | 75 | 4800 | 3/8 x 1/2 | 26.60 |

Caution: Be sure working pressure required does not exceed above ratings. Misapplication can result in serious operator injury. **Note:** Advise product to be handled, maximum temperature and pressure fitting size or sizes when ordering.