

Non-Corrosive Fluid Path

Reeltek Series

New Product Option

DESCRIPTION

Reelcraft now offers a non-corrosive fluid path option on our popular Reeltek reels. These reels are designed to be lighter weight, but rigid enough to withstand industrial use. They are ideal for wall, ceiling, floor, pit or truck mount.

BENEFITS

- **Lighter Weight** composite spool reduces overall weight but maintains structural strength.
- **Added Stability** structural reinforcements throughout make this a robust reel and eliminate the need for a dual base.
- **Trouble-Free** possibility of hose latch-out at full extension has been completely eliminated by mounting the latching mechanism on the guide arm.
- **Long Service Life** Stainless torsion spring ensures maximum life and requires little maintenance.
- **Reduced Wear** by design, the ratchet and latch pawl are substantially thicker than competing reels to reduce wear and increase service life.
- **High Corrosion Resistance** spool is made from an engineered composite material. Fluid path is either all stainless or stainless shaft and CPVC swivel. Base and guide arm are powder coated for maximum corrosion resistance.

RELATED PRODUCTS

Reelcraft offers a full line of hose, cord and cable reels. For a full product listing contact your distributor or visit us on the web at www.reelcraft.com.



RT605-OLB * Model shown with hose.

602062-2



Stainless swivel on most models.

602064-1



CPVC swivel on all models with an asterisk [*].

SPECIFICATIONS

- ✓ Maximum operating temperature 150°F (65°C)
- ✓ Spool is made from lighter weight engineered polymer
- ✓ Base and guide arm are made from heavy gauge steel stampings and reinforced with structural ribbing
- ✓ Full flow shaft and swivel
- ✓ Latching mechanism is mounted on guide arm to prevent latch-out at full hose extension
- ✓ Specially conditioned drive spring
- ✓ Vibration proof self-locking fasteners assure assembly integrity
- ✓ 2-year factory warranty

SPECIFICATIONS

MODEL (without hose)	HOSE I.D.		HOSE O.D.		CAPACITY		PRESSURE		WEIGHT	
	in	mm	in	mm	ft	m	psi	bar	lbs	kg
RT402-OLB	¼	6.4	.500	13	25	8	300	21	19	9
RT403-OLB	¼	6.4	.500	13	35	11	300	21	19	9
RT405-OLB	¼	6.4	.500	13	50	15	300	21	21	10
RT602-OLB	¾	9.5	.640	16	25	8	300	21	19	9
RT603-OLB	¾	9.5	.640	16	35	11	300	21	19	9
RT605-OLB*	¾	9.5	.640	16	50	15	100	7	23	11
RT802-OLB*	½	12.7	.781	20	25	8	100	7	23	11
RT803-OLB*	½	12.7	.781	20	35	11	100	7	23	11
RT805-OLB*	½	12.7	.781	20	50	15	100	7	28	13

NOTE: All prices subject to change, effective January 1, 2008. *Models feature CPVC swivel and stainless shaft. All other models are stainless steel shaft and swivel.



North America: **800-444-3134**

Europe: + 44 (0) 1536 406999

Asia: +63 (45) 625-6624

Latin America: 260-489-1685

www.reelcraft.com

Reelcraft Industries, Inc.

One Reelcraft Center / P.O. Box 248

Columbia City, IN 46725

FAX: **260-248-2605**

Reelcraft Industries is

ISO 9001:2000

Certified Since 1996

REELCRAFT
Wind Things Up With Reelcraft

NON-CORROSIVE FLUID PATH / REELTEK SERIES

Non-Corrosive Fluid Path

Series 5000, 7000 & 9000

New Product Option

DESCRIPTION

The non-corrosive fluid path option offers another level of protection in corrosive environments. Any of the below models designated with an "OLB" ending feature a stainless steel main shaft and swivel. Standard Seals are BUNA but, EPR and VITON are available at additional cost. Reels are shipped less hose and bumper.

BENEFITS

- **Versatility** Guide arms easily adjust to multiple positions and require only standard tools (excludes D9000, payout must be specified at time of order).
- **Stability** Heavy gauge steel and structural reinforcements throughout make these reels robust.
- **Trouble-Free** Field proven cast aluminum ratchet and latch pawl provide reliability and durability (5600 OLS features quiet speed latching mechanism).
- **Long Service Life** Stainless steel main shaft and swivel full flow performance and require little maintenance.
- **High Corrosion Resistance** Steel components are individually powder coated prior to assembly to maximize coverage and corrosion resistance.

RELATED PRODUCTS

The next step in corrosion resistance for highly corrosive environments is Reelcraft's stainless steel line (shown below). Additionally, Reelcraft offers the most comprehensive line of hose, cord and cable reels. For a full product listing contact your distributor or visit us on the web at www.reelcraft.com.



NOTE: For pricing, information and availability of stainless steel reels visit us online at www.REELCRAFT.com.



*Models shown with hose for effect. Actual reels ship less hose and bumper

SPECIFICATIONS

- ✓ Stainless steel main shaft and swivel
- ✓ Maximum operating temperature 150°F (65°C). For higher working temperatures consult factory.
- ✓ Base and guide arm are made from heavy gauge steel stampings and reinforced with structural ribbing
- ✓ Premium grade steel drive spring
- ✓ Corrosion resistant baked-on powder coat finish

- ✓ Vibration proof self-locking fasteners assure assembly integrity
- ✓ 2-year factory warranty
- ✓ Full flow
- ✓ BUNA O-rings

SPECIFICATIONS

MODEL (without hose)	HOSE I.D. in / mm	HOSE O.D. in / mm	CAPACITY ft / m	PRESSURE psi / bar	WEIGHT lbs / kg
SERIES 5000					
5600 OLB	3/8 10	.640 16	35 8	300 21	21
SERIES 7000					
7600 OLB	3/8 10	.640 16	50 15	300 21	41
7800 OLB	1/2 13	.781 20	50 15	300 21	44
SERIES 9000					
D9400 OLB BW	1 25	1.500 38	50 15	50 15	115

NOTE: All prices subject to change, effective January 1, 2008.



NON-CORROSIVE FLUID PATH / SERIES 5000, 7000 & 9000

North America: **800-444-3134**

Europe: + 44 (0) 1536 406999

Asia: +63 (45) 625-6624

Latin America: 260-489-1685

www.reelcraft.com

Reelcraft Industries, Inc.

One Reelcraft Center / P.O. Box 248

Columbia City, IN 46725

FAX: **260-248-2605**

Reelcraft Industries is

ISO 9001:2000

Certified Since 1996

REELCRAFT

Wind Things Up With Reelcraft