

## Multi purpose High Expansion foam concentrate to be proportioned from 3 to 4%

### Description

PLUREX C5 is a synthetic multipurpose foam concentrate based upon fatty alcohols, alkyl sulphates and butyl carbitol. Many fire tests during test programs have shown that it forms a stable foam blanket on burning non polar solvents. It also forms a stable low, medium and high expansion foam which rapidly fills large spaces.

PLUREX C5 foam Concentrate can be used to produce foam with expansion ratios ranging from 50:1 to 1000:1 depending upon the type of generator and its operating pressure. When used with High Expansion or Medium Expansion Generators, recommended proportioning is between 3% and 6% (at 3% = 3 liter of PLUREX C5 with 97 liter water).

### Performance

The performance of PLUREX C5 foam concentrate when used at High Expansion will vary depending upon the performance characteristics of the equipment. Expansion ratios through high expansion generators typically are between 200:1 and 1000:1. For this reason, it is important for the proper design of a high expansion system that the PLUREX C5 foam Concentrate be specifically tested with the foam generators. Medium expansion foam generators typically deliver expansion ratios between 50:1 and 200:1.

PLUREX C5 can be used by most conventional foam equipment such as:

- Balance pressure pump proportioning equipment
- Bladder tank and related proportioners
- Aroundthepump proportioners
- Fixed and portable Inline venturi type inductors
- Fixed or handline nozzles with fixed induction/pick up tubes

### Application

PLUREX C5 is a multi purpose firefighting agent, used in fighting Class A and Class B both indoors and outdoors. It is used only with air aspirating foam discharge devices except when used as a wetting agent on Class A fuels.

When used with high expansion generators, PLUREX C5 is capable of totally flooding large rooms and enclosures allowing it to effectively extinguish horizontal and vertical (three-dimensional) fires.

High expansion foam is also effective in reducing vapor concentrations down wind from hazardous low boiling point gaseous products such as ammonia spills.

When used with medium expansion foam equipment, PLUREX C5 forms a foam blanket which prevents the release of fuel vapor and also provides additional cooling due to the higher water content. Medium expansion foam has benefits in outdoor applications because the foam is less affected by wind conditions.



The foam produced by PLUREX C5 extinguishes hydrocarbon fires best when applied indirectly.

PLUREX C5 is compatible with all foamcompatible dry chemical extinguishing powders.

Sea water can be used without an increase in the application rate.

### Storage and shelf life

PLUREX C5 has an operational temperature range of  $-2^{\circ}\text{C}$  and  $+60^{\circ}\text{C}$ . Limited exposure to temperatures above  $+60^{\circ}\text{C}$  does not affect the firefighting performance.

When stored in the packaging supplied (polyethylene drums or cans) or in equipment recommended by the manufacturer as part of the foam system and within the temperature limits specified, the shelf life of PLUREX C5 concentrate is about 2025 years.

The factors affecting shelf life and stability for SABO foam Agents are discussed in detail in our Technical Bulletin for storage recommendation.

If the product is frozen during storage or transportation, the concentrate should be thawed and used without any de-generation of the performance.

### EcoToxicology and Disposal

PLUREX C5 is environmentally safe and rapidly biodegradable.

### Safety and handling

See our corresponding "Material Safety data sheet".

### Quality insurance

PLUREX C5 – as with all SABO Española – is subject to a very stringent quality controls throughout all stages of production, from incoming raw to the complete product and is manufactured in an ISO 9001:2000 controlled facility. Quality assurance is therefore guaranteed.

### Typical properties

PLUREX C5	Multi purpose Hiex foam
Fire Classes	A and B
Shape and color	Red, clear liquid
Smell	Characteristic, surfactant-alike
Density (20°C)	1,03 $\pm$ 0.02 [g/ml]
pH (concentrate, 20°C)	7,0 $\pm$ 0.5
Viscosity 20°C	7,0 $\pm$ 2,0 [mm <sup>2</sup> /s]
Sediment (EN 1568)	$\leq$ 0,05 [%]
Admixing ratio	3 to 4 [% Vol.] (typical 4%)
Expansion Ratio (EN 15683)	$\geq$ 9.0
Drain Time 25%, (20°C, EN 15683)	$\geq$ 9:00 [min:s]
Drain Time 50%, (20°C, EN 15683)	$\geq$ 15:00 [min:s]
Expansion	Low, Medium , High
Freezing Point	$\leq$ -8 [°C]
Pour Point	$\leq$ -5 [°C]
Recommended storage/Usage temperature	-2 to +60 [°C]

### Ordering information

PLUREX C5 can be supplied in cans, drums, totes or Bulk (contact us for Bulk delivery details).

Part No. F203350C1 25 Liter can Part  
No. F203350D1 200 Liter drum Part  
No. F203350T1 1000 Liter tote