



# YOUTH FIRE BRIGADE

## Industrial Helmet

**Main applications:**

- Apprenticeship at Youth Fire Brigades

**Product benefits:**

- Modern design
- Helmet edge with protective groove guard
- As standard with DJF-logo, optionally with your individual youth fire brigade logo
- Available with 2-point and 4-point chinstrap
- Low weight and optimised protection area
- Easily extended nape section
- With adjustable side vent as standard
- Large printable surfaces
- Increased lateral rigidity through double-walled inner profile
- Imitation leather sweatband as standard



**Outer shell:** Straight helmet shape with rain gutter

**Helmet shell material:**

Duroplastic	Thermoplastic
<input type="checkbox"/> UP-GF glass fibre reinforced unsaturated polyester	<input type="checkbox"/> PF-SF textile/phenolic resin

**HDPE** high-density polyethylene

ABS  
ABS-copolymer

**Alternative suspension:**

Type	AS	Description	SP	P	SB
<input checked="" type="checkbox"/> I/79 GY	-	6-point webbing	-	-	<input checked="" type="checkbox"/>
<input type="checkbox"/> I/80 Y <sup>4</sup>	-	6-point plastic spider	-	<input checked="" type="checkbox"/>	-
<input type="checkbox"/> I/80 B <sup>4</sup>	-	6-point pad-type plastic spider	<input checked="" type="checkbox"/>	-	-
<input type="checkbox"/> I/91 G	-	6-point webbing	-	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/> I/79-4G	-	4-point webbing	-	-	<input checked="" type="checkbox"/>

AS = version for eye protection SP= special padding strips P = padding strips SB = sweatband

**Other helmet equipment (ex works):**

<input type="checkbox"/> Accessory slot 16 mm	<input checked="" type="checkbox"/> Accessory slot 30 mm	<input type="checkbox"/> Integrated eye protector <sup>6</sup>
<input checked="" type="checkbox"/> Side vent (adjustable)	<input type="checkbox"/> Without side vent if required	<input type="checkbox"/> Crown vent
<input checked="" type="checkbox"/> Rain gutter	<input type="checkbox"/> Smaller helmet peak	<input type="checkbox"/> Hole on helmet peak
<input checked="" type="checkbox"/> Sweatband imitation leather <sup>7</sup> (SB)	<input type="checkbox"/> Sweatband natural leather <sup>7</sup> (SB)	<input type="checkbox"/> Sweatband Coolmax® (SB)
<input type="checkbox"/> Lamp holder	<input type="checkbox"/> Cable loop	<input checked="" type="checkbox"/> Chinstrap holder
<input type="checkbox"/> All-round reflective foil	<input type="checkbox"/> Special padding strip white (SP)	<input type="checkbox"/> Special chinstrap

**Adaptable accessories:**

<input type="checkbox"/> Face shield	<input type="checkbox"/> Nape protector	<input type="checkbox"/> Ear defender
<input type="checkbox"/> 2-point chinstrap	<input type="checkbox"/> 4-point chinstrap <sup>8</sup>	<input type="checkbox"/> Special chinstrap
<input type="checkbox"/> Imitation leather sweatband	<input type="checkbox"/> Natural leather sweatband	<input type="checkbox"/> Sweatband Coolmax® (SB)
<input type="checkbox"/> Special padding strip white (SP)		

**Marking surface (for company logo, etc.):**

Method	Front (B x H)	Side (B x H)	Back (B x H)
Hot stamping	<input type="checkbox"/> 6 x 6 cm	<input type="checkbox"/> 9 x 2,5 cm	<input type="checkbox"/> 3 x 3 cm
Pad printing	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**Reference weight:**

Helmet shell size 2: approx. 340 g

**Key:**

- Items supplied/as standard
- Partially as standard
- Optionally available
- Not available

<sup>1</sup> Applies to standard suspensions I/79 G, I/79 GD, I/79-4G, I/79 GY, I/91 G

<sup>2</sup> Only for helmet versions without ventilation

<sup>3</sup> Only in conjunction with suspension I/79 GW

<sup>4</sup> Suspension may not be available with all helmet sizes and helmet colours

<sup>5</sup> For jobs with high heat exposure (in relation to the surrounding atmosphere)

<sup>6</sup> Not for size 2 and suspensions I/79 G (AS version), I/79 GD (AS version), I/80 B, I/52 RENL

<sup>7</sup> Not for suspensions I/80 D, I/80, I/80 Y, I/BC, I/7B; only partially for I/80 B

<sup>8</sup> Only for suspensions I/79 G, I/79 GD, I/79-4G, I/79 GY and AS versions