MB05 MOUNTED BREAKER

STANLEY



The new **MB05** is designed for years of dependable service. The wide flow range let's you go from your skidsteer to miniexcavator with ease. The skidsteer bracket has four positions to allow you to tackle floors and walls.

All models are ready to pin-on or bolt on a custom bracket for your pin grab coupler.



We COVER ALL THE ANGLES you need to get the job done

Four position skid steer mounting bracket

SPECIFICATIONS

| SPECIFICATIONS | | | |
|---------------------------------|---|--------------|--|
| Impact Energy Class | ft - lb | 550 | |
| | J | 750 | |
| Blows Per Minute | bpm | 650 - 1550 | |
| Flow Range | gpm | 10 - 22 | |
| | lpm | 38 - 83 | |
| Hydraulic Operating | psi | 1500 - 2000 | |
| Pressure | bar | 100 - 140 | |
| System Relief Pressure | psi | 3000 | |
| (min. cracking) | bar | 207 | |
| Oil Temperatures (max.) | F | 190 | |
| | С | 88 | |
| Hose Diameter (min.) | inch | 3/4 | |
| | mm | 19 | |
| Adapter Fitting Size and Type | Male JIC 37 degree Flare 1-1/16x12 UNF | | |
| Weight – | lb | 810 | |
| Skid Steer Model (with tool) | kg | 368 | |
| Weight – | lb | 480 | |
| Side Plate Model (with tool) | kg | 218 | |
| Length - Side pLate | inch | 53 | |
| Model (with tool) | mm | 1346 | |
| Tool Diameter | inch | 2.6 | |
| | mm | 67 | |
| Tool Working Length | inch | 15 | |
| | mm | 381 | |
| Main Accumulator | psi | 200 +/- 10 | |
| Charge Pressure | bar | 13.8 +/- 0.7 | |
| Sound Power Level (LW) | dBA | 125 | |
| Carrier Size - Skidsteer | lb | 4500 - 7000 | |
| | kg | 2045 - 3182 | |
| Carrier Size - Excavator | lb | 5000 - 8000 | |
| | kg | 2273 - 3636 | |
| Carrier Size - Backhoe | lb | 6000 - 11000 | |
| | kg | 2727 - 5000 | |
| | | | |

MB05 MOUNTED BREAKER



ORDERING INFORMATION













| MB05 e 00 | MB05 s 02 | MB05 e 04 | MB05 s 04 | MB05 e 05 | MB05 s 05 |
|--|---|--------------------------|------------------------------|-----------------------------|------------------------------|
| Excavator, side plated breaker with 9" pin centers, 7" inner width, 2.25" diameter - with flat top bolt flange for mounting brackets | 4 position skid steer cradle for 9" pin center side plated breaker | Excavator with CP027 top | Skid steer with CP027 top | Excavator with exchange top | Skid steer with exchange top |

ACCESSORIES











| 69863 | 69864 | 69865 | 69866 | 69867 |
|---------|-------------------|------------------|-------|-------------|
| Conical | Chisel, Cross Cut | Chisel, Line Cut | Blunt | Tamping Pad |