



## Specification Sheet

### Double Jacket Contractor's Hose 400 PSI- Rubber Lined 1½", 2", 2½", 3"

### Product Information

Excellent for industrial and construction applications requiring higher working pressure. CD 400 is available in 50', 75', and 100' lengths and exceeds normal requirements set out for contractor hose.



Size	1½"	2"	2½"	3"
Part Number	15CD4	20D6	25CD4	30CD4
Service Test PSI	200 psi	200 psi	200 psi	200 psi
Acceptance Test PSI	400 psi	400 psi	400 psi	400 psi
Bowl Size	1 <sup>15</sup> / <sub>16</sub> "	2 <sup>3</sup> / <sub>8</sub> "	3"	3 <sup>17</sup> / <sub>32</sub> "
Weight per 50' Uncoupled	15.77 lbs	19.76 Lbs	27.04 lbs	32.52 lbs
Weight per 50' Coupled	16.71 lbs	21.20 lbs	29.14 lbs	36.20 lbs

flexibility of the hose, making it easier to use, lay flat, and roll up. Steadfast meets all NFPA 1961 and UL 19 abrasion requirements. Our coating can be applied to any hose we manufacture and is available in Red, Yellow, Orange, Blue, Green, Brown, Tan, Black, and White.



**Testing** - Hydrostatic tests are performed in accordance to ASTM & NFPA 1961 standards.

### Construction

**The Jacket** is evenly and firmly woven with high strength staple polyester yarn and high strength, low elongation filler polyester yarn. It may contain minor visual defects that are not acceptable in DJ 600 & DJ 800 but is more than adequate for contractors and will not compromise jacket integrity.

**The Lining** is EPDM single ply extrusion and is smooth and free of pits and other imperfections and exceeds requirements for contractor hose.

**The Steadfast Coating** provides an environmentally safe coating that enhances our product with superior abrasion resistance and excellent water repellency. Colors are bright and will not easily fade. Being elastic in nature, our coating does not inhibit the natural

**Markings** - Completed assemblies of 50', 75', and 100' lengths are stenciled not less than 4' from each end of the hose using indelible ink. Lettering is at least 1" high stating the name of the manufacturer or coded designation, month and year of manufacture & trade name,