



Specification Sheet

Mill Hose - Single Jacket 250 PSI 1½", 1¾", 2", 2½", 3" and 4"



Product Information

Rubber lined, 100% polyester jacketed Mill Hose is available in 50', 75' and 100' lengths.

flexibility of the hose, making it easier to use, lay flat, and roll up. Steadfast meets all NFPA 1961 and UL 19 abrasion requirements. Our coating can be applied to any hose we manufacture and is available in Red, Yellow, Orange, Blue, Green, Brown, Tan and Black, and White.

Size	1½"	2"	2½"	3"	4"
Part Number	15MS25	20MS25	25MS25	30MS25	40MS25
Service Test PSI	125 psi	125 psi	125 psi	125 psi	125 psi
Acceptance Test PSI	250 psi	250 psi	250 psi	250 psi	250 psi
Bowl Size	1 13/16"	2 5/16"	2 13/16"	3 3/8"	4 3/8"
Weight per 50' Uncoupled	8 lbs	9 lbs	14 lbs	19 lbs	26.5 lbs



Construction

The Jacket is evenly and firmly woven with high strength staple polyester yarn and high strength, low elongation filler polyester yarn. It is seamless and free from physical defects such as lumps, thread knots and irregularities that may compromise the jacket integrity.

The Lining is EPDM single ply extrusion and is smooth and free of pits and other imperfections. Tensile strength, liner elongation and adhesion all meet NFPA 1961.

The Steadfast Coating provides an environmentally safe coating that enhances our product with superior abrasion resistance and excellent water repellency. Colors are bright and will not easily fade. Being elastic in nature, our coating does not inhibit the natural

Testing - Hydrostatic tests are performed in conformance to ASTM, NFPA 1961 and UL-19 testing requirements and standards for hose.