


VUM (Valve Under Monitor)
**V.U.M. RC 4"ANSI X CODE-RPM
W/DRAIN**
AKE112113D

C1/C4-GATED ELBOW C2/C3-BLIND PLUG

\$5095.00 List Price
FEATURES
SPECIFICATIONS

Actuator	Remote Control
Auxiliary Port C1	2.5"NH Gated Elbow Left-Hand
Auxiliary Port C2	Blind Plug
Auxiliary Port C3	Blind Plug
Auxiliary Port C4	2.5"NH Gated Elbow Right-Hand
Drain	W/ Ball Drain
Inlet	4"ANSI 150
Oscillation	No
Outlet	CODE-RPM
Product	Valve Under Monitor (VUM)
Remote Control	Yes
Weight	38.1

DOCUMENTS

Technical Specifications and Drawings

[AKE112113D ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[VALVE UNDER MONITOR SERIES VIDEO \(MP4\)](#)
ABOUT THE VUM (VALVE UNDER MONITOR)

The Valve Under Monitor (VUM) is a lightweight, low friction-loss valve and manifold for installation directly beneath monitors on ladders and platforms. The VUM combines the robust valve mechanism from the TFT Ball Intake Valve with a 4" ANSI 150 inlet and up to four 2.5" outlets. The 2.5" outlets are available with integrated valves, male hose threads or female pipe threads. When paired with a TFT monitor, the monitor flange is omitted for additional weight savings and ease of maintenance. Electric remote controlled (RC) models may be controlled from either a dedicated panel mount control or from TFT RC Monitor Operator Stations.