


**VUM (Valve Under Monitor)**
**V.U.M. WG 4"ANSI X 4"ANSI  
W/DRAIN**
**AKM13111CD**

C1/C2/C3-BLIND PLUG C4-EXTENDED GATED ELBOW

**\$2830.00 List Price**
**FEATURES**
**SPECIFICATIONS**

<b>Actuator</b>	Handwheel on side
<b>Auxiliary Port C1</b>	Blind Plug
<b>Auxiliary Port C2</b>	Blind Plug
<b>Auxiliary Port C3</b>	Blind Plug
<b>Auxiliary Port C4</b>	2.5" NH Extended Gated Elbow Right-Hand
<b>Drain</b>	W/ Ball Drain
<b>Inlet</b>	4"ANSI 150
<b>Oscillation</b>	No
<b>Outlet</b>	4" ANSI 150
<b>Product</b>	Valve Under Monitor (VUM)
<b>Remote Control</b>	No
<b>Weight</b>	34.5

**DOCUMENTS**

Technical Specifications and Drawings

[AKM13111CD ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[VALVE UNDER MONITOR SERIES VIDEO \(MP4\)](#)
**ABOUT THE VUM (VALVE UNDER MONITOR)**

The Valve Under Monitor (VUM) is a lightweight, low friction-loss valve and manifold for installation directly beneath monitors on ladders and platforms. The VUM combines the robust valve mechanism from the TFT Ball Intake Valve with a 4" ANSI 150 inlet and up to four 2.5" outlets. The 2.5" outlets are available with integrated valves, male hose threads or female pipe threads. When paired with a TFT monitor, the monitor flange is omitted for additional weight savings and ease of maintenance. Electric remote controlled (RC) models may be controlled from either a dedicated panel mount control or from TFT RC Monitor Operator Stations.