

No image available

VUM (Valve Under Monitor)

V.U.M. WG 4"ANSI X 4.5"NHM QC W/DRAIN

AKM1Q2113D

C1/C4-GATED ELBOW C2/C3-BLIND PLUG

\$2760.00 List Price

FEATURES

SPECIFICATIONS

Actuator	Handwheel on side
Auxiliary Port C1	2.5"NH Gated Elbow Left-Hand
Auxiliary Port C2	Blind Plug
Auxiliary Port C3	Blind Plug
Auxiliary Port C4	2.5"NH Gated Elbow Right-Hand
Drain	W/ Ball Drain
Inlet	4"ANSI 150
Oscillation	No
Outlet	4.5" NH Male Quick Connect
Product	Valve Under Monitor (VUM)
Remote Control	No
Weight	36.1

DOCUMENTS

Technical Specifications and Drawings

[AKM1Q2113D FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AKM1Q2113D ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[VALVE UNDER MONITOR SERIES VIDEO \(MP4\)](#)

ABOUT THE VUM (VALVE UNDER MONITOR)

The Valve Under Monitor (VUM) is a lightweight, low friction-loss valve and manifold for installation directly beneath monitors on ladders and platforms. The VUM combines the robust valve mechanism from the TFT Ball Intake Valve with a 4" ANSI 150 inlet and up to four 2.5" outlets. The 2.5" outlets are available with integrated valves, male hose threads or female pipe threads. When paired with a TFT monitor, the monitor flange is omitted for additional weight savings and ease of maintenance. Electric remote controlled (RC) models may be controlled from either a dedicated panel mount control or from TFT RC Monitor Operator Stations.