


VUM (Valve Under Monitor)
**V.U.M. PS 4"ANSI X 4"ANSI
W/DRAIN**
AKP131111D
C1/C2/C3/C4-BLIND PLUG
\$1970.00 List Price
FEATURES
SPECIFICATIONS

| | |
|--------------------------|---------------------------|
| Actuator | Hand crank on back |
| Auxiliary Port C1 | Blind Plug |
| Auxiliary Port C2 | Blind Plug |
| Auxiliary Port C3 | Blind Plug |
| Auxiliary Port C4 | Blind Plug |
| Drain | W/ Ball Drain |
| Inlet | 4" ANSI 150 |
| Oscillation | No |
| Outlet | 4" ANSI 150 |
| Product | Valve Under Monitor (VUM) |
| Remote Control | No |
| Weight | 27.1 |

DOCUMENTS

Technical Specifications and Drawings

[AKP131111D FINISHED GOOD PRINT \(ZIP\)](#)
[AKP131111D FINISHED GOOD PRINT \(PDF\)](#)
[AKP131111D FINISHED GOOD PRINT - STEP \(DXF\)](#)
[AKP131111D ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[VALVE UNDER MONITOR SERIES VIDEO \(MP4\)](#)
ABOUT THE VUM (VALVE UNDER MONITOR)

The Valve Under Monitor (VUM) is a lightweight, low friction-loss valve and manifold for installation directly beneath monitors on ladders and platforms. The VUM combines the robust valve mechanism from the TFT Ball Intake Valve with a 4" ANSI 150 inlet and up to four 2.5" outlets. The 2.5" outlets are available with integrated valves, male hose threads or female pipe threads. When paired with a TFT monitor, the monitor flange is omitted for additional weight savings and ease of maintenance. Electric remote controlled (RC) models may be controlled from either a dedicated panel mount control or from TFT RC Monitor Operator Stations.