

No image available

VUM (Valve Under Monitor)

V.U.M. PS 4" ANSI X 4" ANSI W/DRAIN

AKP132511D

C1-GATED ELBOW C2-2.5"NHM

\$2785.00 List Price

FEATURES

SPECIFICATIONS

Actuator	Hand crank on back
Auxiliary Port C1	2.5"NH Gated Elbow Left-Hand
Auxiliary Port C2	2.5"NH Male Threads
Auxiliary Port C3	Blind Plug
Auxiliary Port C4	Blind Plug
Drain	W/ Ball Drain
Inlet	4" ANSI 150
Oscillation	No
Outlet	4" ANSI 150
Product	Valve Under Monitor (VUM)
Remote Control	No
Weight	30.15

DOCUMENTS

Online Videos

[VALVE UNDER MONITOR SERIES VIDEO \(MP4\)](#)

Technical Specifications and Drawings

[AKP132511D ITEM SPECIFICATION \(DOC\)](#)

ABOUT THE VUM (VALVE UNDER MONITOR)

The Valve Under Monitor (VUM) is a lightweight, low friction-loss valve and manifold for installation directly beneath monitors on ladders and platforms. The VUM combines the robust valve mechanism from the TFT Ball Intake Valve with a 4" ANSI 150 inlet and up to four 2.5" outlets. The 2.5" outlets are available with integrated valves, male hose threads or female pipe threads. When paired with a TFT monitor, the monitor flange is omitted for additional weight savings and ease of maintenance. Electric remote controlled (RC) models may be controlled from either a dedicated panel mount control or from TFT RC Monitor Operator Stations.