

No image available

## DUAL BIV 5.0"STORZ X (2) 4.0"STORZ W/PRV

AL22T2P1

FOR TRUCK APPLICATIONS STORZ SWIVEL X STORZ SWIVEL

**\$3360.00 List Price**

### FEATURES

The LDH Gated Wye is a lightweight, low friction-loss valve that can be used in many water distribution applications. Dual robust valve mechanisms from the TFT Ball Intake Valve are streamlined to a large waterway for the ultimate in versatility. Valve seats are field replaceable, devices include a 300 PSI pressure gage and quarter turn air vent and drain valve. Two robust carrying handles make for easy deployment. A polymer bearing ring prevents galvanic corrosion on LDH couplings.

### SPECIFICATIONS

|                               |                  |
|-------------------------------|------------------|
| <b>Coupling Size Side A</b>   | 5" (125 mm)      |
| <b>Coupling Size Side B</b>   | 4" (100mm)       |
| <b>Coupling Swivel Side A</b> | Full Time Swivel |
| <b>Coupling Swivel Side B</b> | Full Time Swivel |
| <b>Handle Type</b>            | Quarter Turn     |
| <b>L D H Inlet</b>            | Yes              |
| <b>L D H Outlet</b>           | Yes              |
| <b>Pressure Relief Valve</b>  | Yes              |
| <b>Type</b>                   | Wyes             |
| <b>Weight</b>                 | 37.1             |

### DOCUMENTS

Technical Specifications and Drawings

[AL22T2P1 ITEM SPECIFICATION \(DOC\)](#)