

No image available

DUAL BIV 4.0"F LH X (2) 6.0"STORZ W/PRV

AL26P2X1

FOR TRUCK APPLICATIONS NON FULL TIME SWIVEL HANDLE
X STORZ SWIVEL

\$3360.00 List Price

FEATURES

The LDH Gated Wye is a lightweight, low friction-loss valve that can be used in many water distribution applications. Dual robust valve mechanisms from the TFT Ball Intake Valve are streamlined to a large waterway for the ultimate in versatility. Valve seats are field replaceable, devices include a 300 PSI pressure gage and quarter turn air vent and drain valve. Two robust carrying handles make for easy deployment. A polymer bearing ring prevents galvanic corrosion on LDH couplings.

SPECIFICATIONS

Coupling Size Side A	4" (100mm)
Coupling Size Side B	6" (150mm)
Coupling Swivel Side A	Non-Full Time Swivel
Coupling Swivel Side B	Storz Swivel
Handle Type	Quarter Turn
Inlet Type	Female Coupling
L D H Inlet	Yes
L D H Outlet	Yes
Pressure Relief Valve	No
Type	Wyes
Weight	41.5

DOCUMENTS

Technical Specifications and Drawings
[AL26P2X1 ITEM SPECIFICATION \(DOC\)](#)