

No image available

3-WAY VALVED MANIFOLD W/PRV

AL32X1

A-6.0"STORZ SWIVEL C-(3) 2.5"M

\$2310.00 List Price

FEATURES

TFT's 3-Way Valved Manifold is a rugged manifold with three 2.5" (64 mm) valved discharge ports, each with a full 2.5" (64 mm) waterway. Maximum operating pressure is 300 psi (21 bar). Valve seats are field replaceable. Quarter turn valve handles operate with low force to move even under pressure. Automatic valve lock keeps its position while flowing at partial openings. Folding handles minimize storage space. Aluminum casting is hardcoat anodized and silver TFT Powder Coat finish inside and out for maximum corrosion protection. Optional adjustable pressure relief valve. Optional rugged .75" (19 mm) air bleed valve to quickly bleed air from the lines or to drain water from the valve housing. Contact TFT customer service for configurations not shown.

SPECIFICATIONS

Coupling Size Side A	6" (150mm)
Coupling Size Side B	2.5" (65 mm)
Coupling Swivel Side A	Full Time Swivel
Handle Type	Quarter Turn
L D H Inlet	Yes
L D H Outlet	No
Pressure Relief Valve	No
Weight	33.8

DOCUMENTS

Technical Specifications and Drawings
[AL32X1 ITEM SPECIFICATION \(DOC\)](#)