

No image available

**HYDRANT VALVES**

**IN-LINE VALVE PARALLEL GB**

**AN3T7T02**

A-5.0" F SWIVEL ROCKER B-5.0" M RIGID

**\$2349.00 List Price**

**FEATURES**

TFT's In-Line Valve is a multi-purpose valve designed for use with 3.5, 4, 4.5 or 5 inch (89, 100, 115, 125 or 150mm) hose. Maximum operating pressure is 250 psi (17bar). Meets 900psi (62 bar) hydrostatic strength test. The aluminum casting are Hardcoat anodized, and powdercoat finished inside and out for maximum corrosion protection. The valve meets NPFA slow close requirements. Optional adjustable pressure relief valve meets NFPA 1901 (2009 edition). Optional rugged 3/4 inch (19mm) air bleed valve quickly bleeds air from the lines or drains water from the valve housing. Contact TFT customer service for configurations not shown.

**SPECIFICATIONS**

<b>Coupling Size Side A</b>	5" (125 mm)
<b>Coupling Size Side B</b>	5" (125 mm)
<b>Coupling Swivel Side A</b>	Full Time Swivel
<b>Coupling Swivel Side B</b>	Rigid
<b>Finish</b>	Stardust Silver
<b>Gear Box Style</b>	Shaft on Top
<b>L D H Inlet</b>	No
<b>L D H Outlet</b>	No
<b>Material</b>	Lightweight Cast Aluminum Alloy
<b>Operation Energy Source</b>	Manual
<b>Pressure Relief Valve</b>	No
<b>Remote Control</b>	No
<b>Size</b>	LDH
<b>Valve Design</b>	Ball Valve Aluminum
<b>Weight</b>	21

**DOCUMENTS**

Instructions For Installation, Safe Operation and Maintenance  
[MANUAL: IN-LINE GAUGE WITH VALVE IN-LINE PIVOTING GAUGE WITH VALVE IN-LINE GAUGE WITH 45° VALVE \(PDF\)](#)

[MANUAL: OASIS HYDRANT ASSIST VALVE \(PDF\)](#)

[VALVE: 2.5INCH QUARTER TURN HYDRANT VALVE MANUAL \(PDF\)](#)

Technical Specifications and Drawings

[AN3T7T02 ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[OASIS HYDRANT VALVE \(MP4\)](#)

## **ABOUT THE HYDRANT VALVES**

TFT's hydrant valve is a lightweight valve with a full, unobstructed 2.5" waterway. 300 psi operating capacity from either side of the valve. TFT's Automatic valve lock keeps the position of the valve while flowing at gated positions and water pressure will never slam the valve shut. The valve is manufactured from an aluminum alloy casting, which is then hard coat anodized and powder coated for maximum corrosion protection. There is a port to install a pressure gauge or a bleeder valve and is available with a quarter turn handle or a slow-close handle to further prevent water hammer.

Please note: When using the filters to search for a product, Side A refers to the inlet/hydrant side of the valve and Side B refers to the outlet/LDH side of the valve.