



HYDRANT VALVES

OASIS HYDRANT ASSIST VALVE W/SHUTOFF

ARS2T2T2T

A/B/C1/C2-5.0"STORZ SWIVEL

\$3608.00 List Price

FEATURES

SPECIFICATIONS

Coupling Size Side A	5" (125 mm)
Coupling Size Side B	5" (125 mm)
Coupling Size Side C1	5" (125 mm)
Coupling Size Side C2	5" (125 mm)
Coupling Swivel Side A	Full Time Swivel
Coupling Swivel Side B	Full Time Swivel
Finish	Stardust Silver
Gear Box Style	Shaft on Top
L D H Inlet	No
L D H Outlet	No
Material	Aluminum
Operation Energy Source	Manual
Pressure Relief Valve	No
Remote Control	No
Size	LDH
Valve Design	Stainless
Weight	36.6

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance
[MANUAL: IN-LINE GAUGE WITH VALVE IN-LINE PIVOTING GAUGE WITH VALVE IN-LINE GAUGE WITH 45° VALVE \(PDF\)](#)

[MANUAL: OASIS HYDRANT ASSIST VALVE \(PDF\)](#)

[VALVE: 2.5INCH QUARTER TURN HYDRANT VALVE MANUAL \(PDF\)](#)

Technical Specifications and Drawings
[ARS2T2T2T2T ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[OASIS HYDRANT VALVE \(MP4\)](#)

ABOUT THE HYDRANT VALVES

TFT's hydrant valve is a lightweight valve with a full, unobstructed 2.5" waterway. 300 psi operating capacity from either side of the valve. TFT's Automatic valve lock keeps the position of the valve while flowing at gated positions and water pressure will never slam the valve shut. The valve is manufactured from an aluminum alloy casting, which is then hard coat anodized and powder coated for maximum corrosion protection. There is a port to install a pressure gauge or a bleeder valve and is available with a quarter turn handle or a slow-close handle to further prevent water hammer.

Please note: When using the filters to search for a product, Side A refers to the inlet/hydrant side of the valve and Side B refers to the outlet/LDH side of the valve.