



**High Rise Kit Series**

**HI RISE VALVE 45 DEG LEFT  
W/ GAUGE**

**AVGSC2LNJNJ**

SLOW CLOSE 0-200 PSI/BAR FIXED OUTLET

**\$1608.00 List Price**

**FEATURES**

TFT's 45-degree standpipe waterway with a left-handle slow close valve, has a full 2.5" (64 mm) waterway for maximum flow with minimal friction loss. The valve handle is on the left side of the waterway and includes a position indicator, which identifies open and close positions. The slow close valve prevents water hammer and allows fine-tuning of the water supply exiting the standpipe. The waterway includes an air bleeder and a protected inline pressure gauge that reads 0 – 200 psi (0-14 bar). The inlet valve body of the waterway swivels 360 degrees before tightening and the body of the inline pressure gauge always swivels 360 degrees for easy connection. The 45-degree angle allows for adaptable installation and it positions the attack hose to prevent kinks.

## SPECIFICATIONS

<b>Coupling Size Side A</b>	2.5" (65 mm)
<b>Coupling Size Side B</b>	2.5" (65 mm)
<b>Coupling Swivel Side A</b>	Full-Time Swivel
<b>Coupling Swivel Side B</b>	Rigid
<b>Finish</b>	Stardust Silver
<b>L D H Inlet</b>	No
<b>L D H Outlet</b>	No
<b>Material</b>	Aluminum
<b>Operation Energy Source</b>	Manual
<b>Pressure Relief Valve</b>	No
<b>Remote Control</b>	No
<b>Size</b>	2.5" (65 mm)
<b>Valve Design</b>	Ball Valve Aluminum
<b>Weight</b>	9.15
<b>Connection Type Side A</b>	NH Female
<b>Connection Type Side B</b>	NH Male
<b>Coupling Style Side B</b>	Male Threads
<b>Coupling Style Side A</b>	Rocker

## ABOUT THE HIGH RISE KIT SERIES

TFT's High Rise Kits are a standpipe valve solution that is configurable to meet your needs. The valve can be customized for a valve handle on the left or right side or setup with no internal valve and use it as a standpipe elbow with pressure gauge. It's an easy one-piece solution that you don't have to piece meal together from three or four pieces; simply connect the valve and you're ready to go. The kits include a compact duffel bag, 2.5" (64 mm) standpipe valve with pressure gauge, (2) spanner wrenches, a 2.5"x1.5" reducer for use with a 1.5" coupled hose off the valve, and a 1.5"x 2.5" increaser for break and extend hose operations off of a ball shutoff valve.

## DOCUMENTS

### Technical Specifications and Drawings

[AVG2ENJNJ FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AVG2ENJNJM FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AVGSC2LNJNJ FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AVGSC2LNJNJ ITEM SPECIFICATION \(DOC\)](#)

[AVGSC2LNJNJM FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AVGSC2RNJNJ FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[AVGSC2RNJNJM FINISHED GOOD PRINT - STEP \(ZIP\)](#)

### Online Videos

[HIGH-RISE KIT SERIES VIDEO \(MP4\)](#)

### Product Brochures

[HIGH-RISE KIT SERIES BROCHURE \(PDF\)](#)

### Service Procedures

[PARTS LIST: IN-LINE GAUGE W/ 45 DEG LEFT \(PDF\)](#)