



## HYDRANT VALVES

### HI-RISE VALVE W/GAUGE 0-300 PSI

AVGSC3SNJNJ

2.5" F SWIVEL ROCKER X PIVOT 2.5" M SLOW CLOSE

**\$1085.00** List Price

#### FEATURES

#### SPECIFICATIONS

<b>Coupling Size Side A</b>	2.5" (65 mm)
<b>Coupling Size Side B</b>	2.5" (65 mm)
<b>Coupling Swivel Side A</b>	Non-Full Time Swivel
<b>Finish</b>	Stardust Silver
<b>L D H Inlet</b>	No
<b>L D H Outlet</b>	No
<b>Material</b>	Aluminum
<b>Operation Energy Source</b>	Manual
<b>Pressure Relief Valve</b>	No
<b>Remote Control</b>	No
<b>Size</b>	2.5" (65 mm)
<b>Valve Design</b>	Ball Valve Aluminum
<b>Weight</b>	9.5

#### DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance  
[MANUAL: IN-LINE GAUGE WITH VALVE IN-LINE PIVOTING GAUGE WITH VALVE IN-LINE GAUGE WITH 45° VALVE \(PDF\)](#)  
[MANUAL: OASIS HYDRANT ASSIST VALVE \(PDF\)](#)  
[VALVE: 2.5INCH QUARTER TURN HYDRANT VALVE MANUAL \(PDF\)](#)

Technical Specifications and Drawings  
[AVGSC3SNJNJ ITEM SPECIFICATION \(DOC\)](#)

Online Videos  
[OASIS HYDRANT VALVE \(MP4\)](#)

Service Procedures  
[PARTS LIST: IN-LINE PIVOT GAUGE W/ VALVE \(PDF\)](#)

#### ABOUT THE HYDRANT VALVES

TFT's hydrant valve is a lightweight valve with a full, unobstructed 2.5" waterway. 300 psi operating capacity from either side of the valve. TFT's Automatic valve lock keeps the position of the valve while flowing at gated positions and water pressure will never slam the valve shut. The valve is manufactured from an aluminum alloy casting, which is then hard coat anodized and powder coated for maximum corrosion protection. There is a port to install a pressure gauge or a bleeder valve and is available with a quarter turn handle or a slow-close handle to further prevent water hammer.

Please note: When using the filters to search for a product, Side A refers to the inlet/hydrant side of the valve and Side B refers to the outlet/LDH side of the valve.