

No image
available

ULTIMATIC 125 Series

ULTIMATIC ER W/PLUG 1.5" F

B-TO-ERP-150

150 PSI CONTROL SPRING

\$1336.00 List Price

FEATURES

SPECIFICATIONS

Remote Control	No
Weight	5.8

DOCUMENTS

Service Procedures

[ULTIMATIC 125 NOZZLE SERVICE POSTER \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[HANDHELD AUTOMATIC PRESSURE CONTROL NOZZLE MANUALS \(PDF\)](#)

[ULTIMATIC ER MONITOR NOZZLES \(PDF\)](#)

[Z FRENCH MANUEL : LANCES PORTABLES AVEC CONTRÔLE AUTOMATIQUE DE PRESSION](#)

Technical Specifications and Drawings

[B-TO-ERP-150 ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[ULTIMATIC F04 \(BP20-131\) 3RD PARTY CERTIFICATION ENGLISH TRANSLATION EN15182-2 TYPE 4.1 PN16 \(PDF\)](#)

[ULTIMATIC F04 \(BP20-131\) 3RD PARTY CERTIFICATION GERMAN LANGUAGE EN15182-2 TYPE 4.1 PN16 \(PDF\)](#)

ABOUT THE ULTIMATIC 125 SERIES

The ULTIMATIC™ is available as either a handheld or electric remote monitor nozzle. It features flush without shutting down, molded rubber bumper with "power fog" teeth, and easily pairs with a number of low and multi-expansion foam attachments.

Handheld: An automatic nozzle available in 100 psi (7 bar) and 75 psi (5 bar) models in 1" (25mm) or 1.5" (38 mm) versions. It is adjustable from a straight stream to a dense fog pattern and includes detent flow control, "Gasket Grabber" inlet screen, patented TFT slide valve, and optional colored pistol grip and handle covers. ULTIMATIC's are also available with TFT's IMPULSE™ trigger valve system.

Monitor Nozzle: A 1.5" (38mm) electric remote nozzle that's available in automatic or selectable flow styles. Flows range from 10-125gpm (40-500 l/min) in several pressure ratings. For use with the EF1 and Tornado monitor series.