



ULTIMATIC 125 Series

SELECTABLE ER W/PLUG 1.5" F

B-TOS-ERP

15 TO 120 GPM @ 100PSI

\$1457.00 List Price

FEATURES

Selectable gallonage nozzle is infinitely adjustable between 15 and 120 gpm @ 100 psi (50-450 l/min at 7 bar). Indexed flow settings are provided at 15 gpm and 50 l/min increments. Flow setting may be adjusted without shutting down or locked to a specific setting as desired. Includes flush without shutting down and molded rubber teeth for full-fill "power fog" pattern. Lightweight hard coat anodized aluminum for maximum resistance to corrosion and wear. Accepts both FJ-U FOAMJET low-expansion and FJ-UMX FOAMJET multi-expansion foam attachments. 1.5" NH (38mm) swivel coupling is standard. For use on TFT Tornado and EF1 RC monitor only.

SPECIFICATIONS

| | |
|------------------------------|--------------------------|
| Valve Design | No Valve |
| Flow Rate | 15-120gpm (40-450 l/min) |
| Inlet Coupling Style | Rocker |
| Inlet Coupling Swivel | Swivel |
| Pressure Mode | Single |
| Type | Selectable |
| Operating Pressure | 100psi (7bar) |
| Remote Control | No |
| Weight | 5.9 |
| Bumper Material | Rubber - bonded |
| Certification | CE |

DOCUMENTS

Service Procedures

[ULTIMATIC 125 NOZZLE SERVICE POSTER \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[ER SELECTABLE NOZZLE INSTRUCTIONS \(PDF\)](#)

[HANDHELD AUTOMATIC PRESSURE CONTROL NOZZLE MANUALS \(PDF\)](#)

[ULTIMATIC ER MONITOR NOZZLES \(PDF\)](#)

[Z FRENCH MANUEL : LANCES PORTABLES AVEC CONTRÔLE AUTOMATIQUE DE PRESSION](#)

Technical Specifications and Drawings

[B-TOS-ERP FINISHED GOOD PRINT \(ZIP\)](#)

[B-TOS-ERP FINISHED GOOD PRINT - STEP \(DXF\)](#)

[B-TOS-ERP ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[ULTIMATIC F04 \(BP20-131\) 3RD PARTY CERTIFICATION ENGLISH TRANSLATION EN15182-2 TYPE 4.1 PN16 \(PDF\)](#)

[ULTIMATIC F04 \(BP20-131\) 3RD PARTY CERTIFICATION GERMAN LANGUAGE EN15182-2 TYPE 4.1 PN16 \(PDF\)](#)

ABOUT THE ULTIMATIC 125 SERIES

The ULTIMATIC™ is available as either a handheld or electric remote monitor nozzle. It features flush without shutting down, molded rubber bumper with "power fog" teeth, and easily pairs with a number of low and multi-expansion foam attachments.

Handheld: An automatic nozzle available in 100 psi (7 bar) and 75 psi (5 bar) models in 1" (25mm) or 1.5" (38 mm) versions. It is adjustable from a straight stream to a dense fog pattern and includes detent flow control, "Gasket Grabber" inlet screen, patented TFT slide valve, and optional colored pistol grip and handle covers. ULTIMATIC's are also available with TFT's IMPULSE™ trigger valve system.

Monitor Nozzle: A 1.5" (38mm) electric remote nozzle that's available in automatic or selectable flow styles. Flows range from 10-125gpm (40-500 l/min) in several pressure ratings. For use with the EF1 and Tornado monitor series.