



**BUBBLECUP Series**

**BUBBLE CUP TIP 1.0\"/>**

**D1024BC**

10&24 GPM FOAM ASPIRATING SLEEVE

**\$272.00 List Price**

**FEATURES**

Dual gallonage Bubble Cup nozzle with two flow settings of 10 and 24 gpm @ 100 psi (37 and 90 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1.0" NH (25mm) rigid thread is standard.

**SPECIFICATIONS**

<b>Pistol Grip</b>	No
<b>Valve Design</b>	Twist Style Baffle
<b>Flow Rate</b>	10/24 gpm (37/90 l/min)
<b>Break Apart Style</b>	Tip Only
<b>Inlet Coupling Style</b>	Knurled
<b>Body Size</b>	1" (25 mm)
<b>Inlet Coupling Swivel</b>	Rigid
<b>Style</b>	Break-Apart
<b>Pressure Mode</b>	Single
<b>Type</b>	Selectable
<b>Operating Pressure</b>	100 psi (7 bar)
<b>Remote Control</b>	No
<b>Weight</b>	0.9
<b>Bumper Material</b>	Metal - aluminum

**DOCUMENTS**

Service Procedures

- [1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)
- [1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

- [D1024BC FINISHED GOOD PRINT \(PDF\)](#)
- [D1024BC FINISHED GOOD PRINT - STEP \(DXF\)](#)
- [D1024BC ITEM SPECIFICATION \(DOC\)](#)
- [ER BUBBLECUP EXPLODED VIEW \(PDF\)](#)
- [PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)
- [PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

- [BUBBLECUP & TWISTER INSTRUCTION MANUAL \(PDF\)](#)
- [ER BUBBLE CUP® NOZZLES \(PDF\)](#)
- [Z FRENCH MANUEL : LANCES TWISTER® ET BUBBLECUP® \(PDF\)](#)
- [Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

Online Videos

- [BUBBLE CUP SERIES VIDEO \(MP4\)](#)

Product Brochures

- [BUBBLE CUP SERIES \(PDF\)](#)

## **ABOUT THE BUBBLECUP SERIES**

A unique combination nozzle capable of producing aspirated finished foam, conventional straight stream and a wide fog pattern. It's available as a handheld nozzle or an electric remote monitor nozzle that's perfect for TFT's EF1 monitor.

**Handheld:** The 1" (25mm) version is a dual gallonage foam nozzle while the 1.5" (38mm) version is available as either a single or dual gallonage foam nozzle. To use the built-in aspirating feature of the nozzle, the operator slides the outer sleeve forward, and by adjusting the pattern, has control of reach and aspiration of the finished foam. If an immediate wide fog pattern is needed, the sleeve can be retracted and adjusted instantly to its regular position.

**Monitor Nozzle:** An electric remote nozzle that's available in a 20/60 gpm (75/225 l/min) or 20/95 gpm (75/360 l/min) version and includes an integrated shutoff built into the nozzle. The integrated retractable aspirating sleeve allows quick and easy foam aspiration. Control with a Bluetooth device or joystick.

[\*\*Do you even need a firefighting nozzle?\*\*](#)