



### **TWISTER Series**

## TWISTER TIP 1.0"F

D1040

10&40 GPM DUAL GALLONAGE

\$98.00 List Price

#### **FEATURES**

Dual gallonage nozzle with two flow settings of 10 and 40 gpm @ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. This tip only design has a twist "off" position for break-and-extend operations. 1" NH (25mm) rigid thread is standard.

### **SPECIFICATIONS**

Pistol Grip	No
Valve Design	Twist Style Baffle
Flow Rate	10/40 gpm (37/150 l/min)
Break Apart Style	Tip Only
Inlet Coupling Style	Knurled
Body Size	1" (25 mm)
Inlet Coupling Swivel	Rigid
Style	Break-Apart
Pressure Mode	Single
Туре	Selectable
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	0.6
Bumper Material	Rubber - press fit

### **DOCUMENTS**

Service Procedures

1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE (PDF)
1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE (PDF)

**Technical Specifications and Drawings** 

C1024 ITEM SPECIFICATION (DOC)

D1040 FINISHED GOOD PRINT (PDF)

D1040 FINISHED GOOD PRINT - STEP (DXF)

D1040 ITEM SPECIFICATION (DOC)

PARTS LIST: D SERIES TWISTER AND BUBBLECUP (PDF)

PARTS LIST: F SERIES TWISTER AND BUBBLECUP (PDF)

Instructions For Installation, Safe Operation and Maintenance Z Spanish Manual: Boquillas Twister® and Bubblecup® (PDF)

**Product Brochures** 

SINGLE FLOW TWISTER PRODUCT BROCHURE (PDF)

# **ABOUT THE TWISTER SERIES**

The Twister is available as a selectable, dual gallonage, combination nozzle and a fixed flow 95 gpm flow rate. Designed for simplicity and durability, the rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.

Learn More: Do you even need a firefighting nozzle?