



TWISTER Series

TWISTER NOZZLE 1.0" F

DS1040

10&40 GPM DUAL GALLONAGE

\$305.00 List Price

FEATURES

Dual gallonage nozzle with two flow settings of 10 and 40 gpm @ 100 psi (37 and 150 l/min @ 7 bar). All lightweight materials, hard coat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Rocker lug 1" NH (25mm) swivel is standard.

SPECIFICATIONS

Pistol Grip	No
Valve Design	Stainless
Flow Rate	10/40 gpm (37/150 l/min)
Inlet Coupling Style	Rocker
Body Size	1" (25 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	1.8
Bumper Material	Rubber - press fit

DOCUMENTS

Service Procedures

[1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

[1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

[C1024 ITEM SPECIFICATION \(DOC\)](#)

[DS1040 FINISHED GOOD PRINT \(PDF\)](#)

[DS1040 FINISHED GOOD PRINT - STEP \(DXF\)](#)

[DS1040 ITEM SPECIFICATION \(DOC\)](#)

[PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

[PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

ABOUT THE TWISTER SERIES

A selectable, dual gallonage, combination nozzle available in ¾" (19mm), 1" (25mm) and 1.5" (38mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.