



SMOOTHBORE Series

NFPA STACK TIP 1.5”F

FS-3STACK

TIP SIZES 1-1/4" 1-1/8" 1.0" PER NFPA 1901

\$198.00 List Price

FEATURES

These lightweight tips are hard coat anodized, and have pressure/flow charts laser engraved on each tip. Orifice openings are 1-1/4, 1-1/8", and 1" (32mm, 28mm and 25mm). Use with valved playpipe H-2VPP for compliance with NFPA 1901 equipment requirements. Each tip is threaded 1.5" NH (38mm).

SPECIFICATIONS

Pistol Grip	No
Inlet Coupling Style	Rocker
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Rigid
Type	Smoothbore
Remote Control	No
Weight	1.3

DOCUMENTS

Technical Specifications and Drawings

[FS-3STACK FINISHED GOOD PRINT \(PDF\)](#)

[FS-3STACK FINISHED GOOD PRINT - STEP \(DXF\)](#)

[FS-3STACK ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures

[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

ABOUT THE SMOOTHBORE SERIES

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.