



**TWISTER Series**

**TWISTER W/GRIP 1.5" F**

**FS2095P**

20&95 GPM @ 100 PSI DUAL GALLONAGE

**\$475.00 List Price**

**FEATURES**

Dual gallonage nozzle with two flow settings of 20 and 95 gpm @ 100 psi (75 and 360 l/min @ 7bar). All lightweight materials, hard coat anodized aluminum. Quick-change rear valve seat, stainless steel shut-off ball and a twist "off" position for positive shut off. Pistol grip is mounted below the valve. Rocker lug 1.5" NH (38mm) swivel is standard.

**SPECIFICATIONS**

<b>Pistol Grip</b>	Yes
<b>Valve Design</b>	Stainless
<b>Flow Rate</b>	20/95 gpm (75/360 l/min)
<b>Inlet Coupling Style</b>	Rocker
<b>Body Size</b>	1.5" (38 mm)
<b>Inlet Coupling Swivel</b>	Non-Full Time Swivel
<b>Style</b>	One Piece with Valve
<b>Pressure Mode</b>	Single
<b>Type</b>	Selectable
<b>Operating Pressure</b>	100 psi (7 bar)
<b>Remote Control</b>	No
<b>Weight</b>	2.6
<b>Bumper Material</b>	Rubber - press fit

**DOCUMENTS**

Service Procedures

- [1" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)
- [1.5" TWISTER & BUBBLECUP SERIES SERVICE PROCEDURE \(PDF\)](#)

Technical Specifications and Drawings

- [C1024 ITEM SPECIFICATION \(DOC\)](#)
- [FS2095P FINISHED GOOD PRINT \(PDF\)](#)
- [FS2095P FINISHED GOOD PRINT - STEP \(DXF\)](#)
- [FS2095P ITEM SPECIFICATION \(DOC\)](#)
- [PARTS LIST: D SERIES TWISTER AND BUBBLECUP \(PDF\)](#)
- [PARTS LIST: F SERIES TWISTER AND BUBBLECUP \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

- [Z SPANISH MANUAL: BOQUILLAS TWISTER® AND BUBBLECUP® \(PDF\)](#)

**ABOUT THE TWISTER SERIES**

A selectable, dual gallonage, combination nozzle available in ¾" (19mm), 1" (25mm) and 1.5" (38mm) threads and is designed for simplicity and durability. The rubber bumper provides a positive grip and protects the front end. Twisting the shaper from the off position produces the following settings: low flow straight stream, low flow narrow fog, high flow straight stream, and high flow fog. The rugged, economical nozzle also accepts the FoamJet multi-expansion foam aspirating attachment.