



**SMOOTHBORE Series**

**NEW YORK STACK TIP 1.5" F**

**FSNYSTACK**

TIP SIZES 15/16" & 1/2" TIP SIZES

**\$151.00 List Price**

**FEATURES**

15/16" (24mm) and 1/2" (12mm) Dual stacked tips. Base tip has a 15/16" (24mm) bore with 1.5" (38mm) NH female thread inlet. Top tip has a 1/2" (13mm) bore with male threads. Base tip outlet has female threads for durability. Easy to read pressure/flow charts are laser engraved. 1.5" NH (38mm) inlet thread is standard.

**SPECIFICATIONS**

<b>Pistol Grip</b>	No
<b>Inlet Coupling Style</b>	Knurled
<b>Body Size</b>	1.5" (38 mm)
<b>Inlet Coupling Swivel</b>	Rigid
<b>Type</b>	Smoothbore
<b>Remote Control</b>	No
<b>Weight</b>	0.6

**DOCUMENTS**

Technical Specifications and Drawings

[FSNYSTACK FINISHED GOOD PRINT \(PDF\)](#)

[FSNYSTACK ITEM SPECIFICATION \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures

[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

**ABOUT THE SMOOTHBORE SERIES**

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.