

No image  
available

**THUNDERFOG Series**

**THUNDERFOG W/GRIP  
2.5" BICM**

FTS-EWPS-BIC

110-750 LPM @ 700 KPA 7 BAR SPINNING TEETH

**\$1185.00 List Price**

**FEATURES**

**SPECIFICATIONS**

<b>Pistol Grip</b>	Yes
<b>Valve Design</b>	Stainless
<b>Flow Rate</b>	110-750gpm
<b>Body Size</b>	2.5" (65 mm)
<b>Inlet Coupling Swivel</b>	Full-Time Swivel
<b>Style</b>	One Piece with Valve
<b>Pressure Mode</b>	Single
<b>Type</b>	Selectable
<b>Fog Teeth</b>	Spinning
<b>Operating Pressure</b>	100psi (7bar)
<b>Remote Control</b>	No
<b>Weight</b>	5.9
<b>Bumper Material</b>	Rubber - bonded
<b>Certification</b>	NFPA/FM

**DOCUMENTS**

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

[Z INDONESIAN THUNDERFOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

Online Videos

[THUNDERFOG SERIES VIDEO \(MP4\)](#)

**ABOUT THE THUNDERFOG SERIES**

A selectable gpm nozzle that is available in two basic series: the 200 series, with a selectable flow range of 30-200 gpm (110-750 l/min), or 95-250gpm (360-950 l/min) and the 250 series, with a selectable flow range of 95-250 gpm (360-950 l/min). The 200 series is an excellent choice for 1.5", 1.75", or 2.0" hose lines, and for higher flows, the 250 series will work with 2.5" or 3.0" hose lines. All THUNDERFOGS are NFPA compliant, and are available in tip only configuration, with stainless steel ball shutoff, or with a Playpipe. Optional colored pistol grips and handle covers are available to match all NFPA approved colors. They accept the FJ-MX-FT FOAMJET multi-expansion foam aspirating attachment, and are available with your choice of a molded rubber bumper or stainless steel spinning fog teeth.