



G-FORCE Series

G-FORCE 1.5\"/>

GF1A1F

FIXED 150 GPM @ 100 PSI FIXED FOG TEETH

\$714.00 Guaranteed US Price

FEATURES

SPECIFICATIONS

| | |
|------------------------------|----------------------|
| Pistol Grip | No |
| Break Apart Size | 1.5" |
| Flow Rate | 150 gpm (565 l/min) |
| Break Apart Style | Tip Only |
| Inlet Coupling Style | Rocker |
| Body Size | 1.5" (38 mm) |
| Inlet Coupling Swivel | Non-Full Time Swivel |
| Style | Break-Apart |
| Pressure Mode | Single |
| Type | Fixed |
| Fog Teeth | Fixed |
| Operating Pressure | 100 psi (7 bar) |
| Remote Control | No |
| Weight | 3.3 |
| Bumper Material | Rubber - bonded |
| Certification | NFPA/FM |
| Inlet Connection Type | NH Female |

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)

[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)

[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)

[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Technical Specifications and Drawings

[GF1A1F FINISHED GOOD PRINT - STEP \(ZIP\)](#)

Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)

[G-FORCE SPANISH CATALOG \(PDF\)](#)

[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)

[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)

[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)

[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)

[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**V**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.