



G-FORCE Series

G-FORCE 1.5" F TIP

GF1D1F

SEL 30/60/95/125/150 GPM @ 75 PSI FIXED FOG TEETH

\$714.00 Guaranteed US Price

FEATURES

SPECIFICATIONS

Pistol Grip	No
Break Apart Size	1.5"
Flow Rate	30/60/95/125/150gpm (110/230/360/470/570 l/min)
Break Apart Style	Tip Only
Inlet Coupling Style	Rocker
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Non-Full Time Swivel
Style	Break-Apart
Pressure Mode	Single
Type	Selectable
Fog Teeth	Fixed
Operating Pressure	75psi (5bar)
Remote Control	No
Weight	3.3
Bumper Material	Rubber - bonded
Inlet Connection Type	NH Female

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)

[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)

[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)

[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)

[G-FORCE SPANISH CATALOG \(PDF\)](#)

[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)

[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)

[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)

[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)

[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**V**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.