


G-FORCE Series
**G-FORCE 1.5" F VALVE W/GRIP
GF3C1S**

SEL 30/60/95/125/150 GPM @ 100 PSI SPINNING TEETH

\$655.00 Guaranteed US Price
FEATURES

Selectable Flow with Fixed Pressure Optimal straight stream and fog pattern performance are achieved at the selected flow and the single rated pressure. Stainless steel spinning for teeth.

SPECIFICATIONS

| | |
|------------------------------|--|
| Pistol Grip | Yes |
| Flow Rate | 30/60/95/125/150gpm (110/230/360/470/570 l/min) |
| Inlet Coupling Style | Rocker |
| Body Size | 1.5" (38 mm) |
| Inlet Coupling Swivel | Full-Time Swivel |
| Style | One Piece with Valve |
| Pressure Mode | Single |
| Type | Selectable |
| Fog Teeth | Spinning |
| Operating Pressure | 100 psi (7 bar) |
| Remote Control | No |
| Weight | 4.5 |
| Bumper Material | Rubber - bonded |
| Certification | NFPA/FM |
| Inlet Connection Type | NH Female |

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)
[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)
[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)
[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)
[G-FORCE SPANISH CATALOG \(PDF\)](#)
[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)
[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)
[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)
[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)
[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**V**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.