


G-FORCE Series
**G-FORCE 1.5" BSPF VALVE
W/GRIP**
GPB3A2S-01

SEL 100/250/500 LPM @ 6 BAR SPINNING TEETH

\$714.00 Guaranteed US Price
FEATURES

Nozzle with integral valve and pistol grip provides turbulence free flow control and five detent flow positions. Automatic Pressure / Variable Flow Optimal straight stream and fog pattern performance are achieved over the rated flow range at the rated pressure. Stainless steel spinning for teeth.

SPECIFICATIONS

Pistol Grip	Yes
Flow Rate	100/250/500 l/min
Inlet Coupling Style	1.5 inch BSP Female
Body Size	1.5" (38mm)
Inlet Coupling Swivel	Full-Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Type	Selectable
Fog Teeth	Spinning
Operating Pressure	5 bar (75 psi)
Remote Control	No
Weight	4.5
Bumper Material	Rubber - bonded
Certification	EN
Inlet Connection Type	BSP Female

DOCUMENTS

Service Procedures

[G-FORCE G903-KIT: G-FORCE VALVE PLUG SERVICE PROCEDURE \(PDF\)](#)
[HOW TO REPLACE A 1- G-FORCE SHAPER \(MP4\)](#)
[HOW TO REPLACE THE BAIL HANDLE ON G-FORCE NOZZLE](#)
[IMPULSE™ TRIGGER VALVE SYSTEM MAINTENANCE AND SERVICE PROCEDURE \(PDF\)](#)

Product Brochures

[Z ARABIC G-FORCE \(PDF\)](#)

Product Catalogs

[G-FORCE CATALOG \(PDF\)](#)
[G-FORCE SPANISH CATALOG \(PDF\)](#)
[Z FRENCH G-FORCE FRENCH CATALOG \(PDF\)](#)
[Z GERMAN G-FORCE GESAMTKATALOG \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[G-FORCE MANUAL: FIXED & SELECTABLE AND AUTOMATIC \(PDF\)](#)
[INTERNATIONAL G-FORCE NOZZLE FIXED, SELECTABLE, AUTOMATIC AND AUTOMATIC WITH FLOW LIMITING MANUAL](#)
[Z ITALIAN G-FORCE MANUAL: INTERNATIONAL G-FORCE NOZZLE \(PDF\)](#)
[Z SPANISH G-FORCE MANUAL: BOQUILLA INTERNACIONAL G-FORCE \(PDF\)](#)

Certifications & Approvals

[G-FORCE \(GP**Y**\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)
ABOUT THE G-FORCE SERIES

Based on a highly customizable global nozzle platform design, the unique G-Force® series of fixed, selectable, and automatic nozzles combine over 40 years of Task Force Tips design innovation and experience into true next generation firefighting tools. Available in a 1" (25mm) and 1.5" (38mm) versions, the nozzles incorporate unique performance components such as a stainless steel slide valve, inlet debris screen and protective fog pattern choices. The G-Force® series deliver high performance and rugged dependability in a low cost package.