



VIT BALL VALVE Series

**PLAYPIPE W/VALVE
2.5" FEMALE X 1.5" MALE
H-2VPP**

\$1041.00 List Price

FEATURES

Valved playpipe with 6 detent flow positions, ball-type shutoff, and optional color coded handle covers. Rubber-coated, easy grip handles are designed to reduce fatigue. 2.5" (64mm) NH rocker lug full-time swivel inlet coupling, 1.5" (38mm) NH male outlet is standard. Use with FS-3STACK stack tip set for compliance with NFPA 1901 equipment requirements.

SPECIFICATIONS

Pistol Grip	No
Inlet Coupling Style	2.5" NH Female
Body Size	2.5" (65 mm)
Inlet Coupling Swivel	Full Time Swivel
Outlet Diameter	1 3/8" (35 mm)
Remote Control	No
Weight	7.5
Connection Type Side A	NH Female
Connection Type Side B	NH Male
Outlet Coupling Style	Male Threads
Outlet Coupling Swivel	Rigid

DOCUMENTS

Technical Specifications and Drawings

[H-2VPP FINISHED GOOD PRINT \(PDF\)](#)

[H-2VPP FINISHED GOOD PRINT - STEP \(DXF\)](#)

[H-2VPP ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[HAND HELD BALL VALVE & DETENT STYLE BALL VALVES \(PDF\)](#)

[VALVE INTEGRAL TIP \(VIT\) NOZZLE MANUAL \(PDF\)](#)

ABOUT THE VIT BALL VALVE SERIES

TFT's VIT (Valve Integral Tip) Ball Valve series is designed to be the most rugged valve/smooth bore tip combination available while still maintaining a competitively low price. By using high strength materials, this unique TFT valve/tip combination provides the maximum amount of resistance to wear and corrosion while offering complete fire streams management flexibility. Designed to provide maximum flow, stream quality, and versatility when coupled with a high flowing combination nozzle, the VIT series can also be used as a smooth bore nozzle. Designed for 1.5", 1.75", 2", 2.5", and 3" (38mm, 52mm, 65mm, and 75mm) attack lines, the VIT series is engineered to meet your high flow needs.