



HANDLINF Series

HANDLINE W/GRIP 1.5"F

H-VPGI

95-300 GPM @ 100 PSI GRIP UNDER VALVE

\$1490.00 List Price

FEATURES

Automatic 100 psi (7 bar) pressure control with a flow capacity of 95-300 gpm (360-1150 l/min). Includes flush without shutting down, patented slide-type valve for turbulence-free flow control, six detent flow positions, molded rubber teeth for full-fill "power fog", and "Gasket Grabber" inlet screen. Pistol grip is mounted below the valve. Lightweight hard coat anodized aluminum materials for maximum resistance to corrosion and wear.1.5" NH (38mm) rocker lug full-time swivel coupling is standard.

SPECIFICATIONS

Pistol Grip	Yes
Valve Design	Stainless Slide Valve
Flow Rate	95-300gpm (360-1150 I/min)
Inlet Coupling Style	Rocker
Body Size	1.5" (38 mm)
Inlet Coupling Swivel	Full Time Swivel
Style	One Piece with Valve
Pressure Mode	Single
Туре	Automatic
Fog Teeth	Fixed
Operating Pressure	100 psi (7 bar)
Remote Control	No
Weight	7
Bumper Material	Rubber - bonded
Inlet Connection Type	NH Female

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance
HANDHELD AUTOMATIC PRESSURE CONTROL NOZZLE MANUALS (PDF)
Z FRENCH MANUEL: LANCES PORTABLES AVEC CONTRÔLE
AUTOMATIQUE DE PRESSION
Z RUSSIAN HANDLINE PARTIAL GRIP, LABELS AND HANDLE (PDF)

Technical Specifications and Drawings
H-VPGI FINISHED GOOD PRINT (PDF)
H-VPGI FINISHED GOOD PRINT (ZIP)
H-VPGI FINISHED GOOD PRINT - STEP (DXF)
H-VPGI ITEM SPECIFICATION (DOC)

Online Videos

HANDLINE SERIES VIDEO (MP4)

Product Brochures

HANDLINE SERIES AUTOMATIC NOZZLES (PDF)

ABOUT THE HANDLINE SERIES

The automatic TFT HANDLINE includes all conventional handline sizes in one. The wide flow range of 95-300 gpm (360-1150 l/min)includes operational pressure choices of 100 psi (7 bar), 75 psi (5 bar) and 55 psi (4 bar). This series is an excellent choice for 1.5"- 2.5" (38mm – 65mm) hose lines. The HANDLINES feature flush without shutdown, "Gasket Grabber" inlet screen, molded rubber bumper with "power fog" teeth, TFT's patented stainless steel slide valve, detent flow control and optional colored pistol grip and handle covers. All TFT HANDLINES accept low- or multi-expansion foam attachments.