



**SMOOTHBORE Series**

**3 STACKED TIPS - 2.5FEMALE INLET**

**MST-3NJ**

1-1/2" 1-1/4" & 1" TIP DIAMETERS

**\$470.00 List Price**

**FEATURES**

Hard coat anodized aluminum alloy for maximum corrosion protection. Flow charts for each tip are lasered. Tip sizes are 1.5", 1.25", and 1.0" (38, 32 and 25mm) diameter. Small tips may be removed for break and extend operations with a 1.5" NH (38mm) hose thread. Standard swivel inlet is 2.5" NH (64mm).

**SPECIFICATIONS**

<b>Inlet Coupling Style</b>	Rocker
<b>Body Size</b>	2.5" (65 mm)
<b>Style</b>	Smoothbore
<b>Remote Control</b>	No
<b>Weight</b>	2.3
<b>Connection Type</b>	NH Female
<b>Coupling Size</b>	2.5" (65 mm)
<b>Coupling Swivel</b>	Non-Full Time Swivel
<b>Orifice Sizes</b>	1.5" (38 mm) 1.25" (32 mm) 1" (25 mm)

**DOCUMENTS**

Technical Specifications and Drawings

[MST-3NJ FINISHED GOOD PRINT \(PDF\)](#)

[MST-3NJ FINISHED GOOD PRINT \(ZIP\)](#)

[MST-3NJ FINISHED GOOD PRINT - STEP \(DXF\)](#)

[MST-3NJ ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[SMOOTH BORE / VIT INSERTS KIT \(PDF\)](#)

Product Brochures

[SMOOTH BORE SERIES FIXED FLOW ATTACK \(PDF\)](#)

**ABOUT THE SMOOTHBORE SERIES**

Engineered with a smooth, tapered waterway, TFT's smooth bore tips provide the stream quality, reach, and penetration that you have come to expect from a traditional smooth bore. Engineered for performance and durability, all smooth bore tips are manufactured from aluminum alloy which is then hard coat anodized, the critical orifice of the smooth bore is recessed 1/8" back into the taper, and an aluminum bumper is machined around the outside of that same edge to prevent damage to the critical orifice edge. The smooth bore size and an easy to read pressure/flow chart is laser engraved on each smooth bore tip to identify which smooth bore will meet your tactical needs on the fireground.