



**QUADRAFOG Series**

**QUADRAFOG 400 W/GRIP  
2.0" BSPM**

**QF400**

70-400 LPM @ 6 BAR FLASHOVER

**\$1010.00 List Price**

**FEATURES**

**SPECIFICATIONS**

<b>Pistol Grip</b>	Yes
<b>Flow Rate</b>	100-400 l/min
<b>Body Size</b>	2" (60mm)
<b>Inlet Coupling Swivel</b>	Swivel
<b>Pressure Mode</b>	Single
<b>Type</b>	Selectable
<b>Operating Pressure</b>	85psi (6bar)
<b>Remote Control</b>	No
<b>Weight</b>	3.8

**DOCUMENTS**

Service Procedures

[QUADRAFOG SERVICE PROCEDURE \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[QUADRAFOG & THUNDERFOG, & QUADRACUP INSTRUCTION MANUAL \(PDF\)](#)

[Z FRENCH MANUEL: THUNDERFOG, QUADRAFOG AND QUADRACUP \(PDF\)](#)

Online Videos

[QUADRAFOG SERIES VIDEO \(MP4\)](#)

Product Brochures

[QUADRAFOG AND THUNDERFOG SELECTABLE GALLONAGE NOZZLES \(PDF\)](#)

Certifications & Approvals

[QUADRAFOG 1000 \(QF1000-SL\) PN 16 EN15182-2 TYPE3 \(PDF\)](#)

[QUADRAFOG 150 PN40 EN15182-4 \(PDF\)](#)

Technical Specifications and Drawings

[QF400 FINISHED GOOD PRINT \(PDF\)](#)

**ABOUT THE QUADRAFOG SERIES**

An excellent selectable gallonage nozzle for any 1" (25mm) or 1.5" (38mm) hose line. The QUADRAFOG is an economical and lightweight combination nozzle suitable for use with low-expansion or multi-expansion foam attachments. 1" versions range are 5-40 gpm (20-150 l/min) or 5-60gpm (20-230 l/min). The 1.5" version has a range of 30-125 gpm (110-470 l/min), and is available in high(100 psi) or low-pressure(75 psi) versions with either a molded rubber bumper or stainless steel spinning fog teeth.