



EDUCTOR Series

EDUCTOR 125 GPM 2.5"NH F X 1.5"NH M

UE-125-NJ-NF

W/36" HOSE .25% .5% 1% 3% 6%

\$1020.00 List Price

FEATURES

full-time swivel rocker lug inlet coupling and 1.5" NH (38mm) male outlet is standard.

SPECIFICATIONS

| | |
|-------------------------------|---------------------|
| Flow Rate | 125 gpm (475 l/min) |
| Inlet | 2.5" (65 mm) |
| Inlet Coupling Style | Rocker |
| Inlet Coupling Swivel | Full Time Swivel |
| Outlet | 1.5" (38 mm) |
| Outlet Coupling Style | Male Threads |
| Outlet Coupling Swivel | Rigid |
| Pressure | 200psi (14bar) |
| Weight | 4.982 |

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

[EDUCTOR - 350 SERIES: IN-LINE FOAM EDUCTOR \(PDF\)](#)

[EDUCTOR, IN-LINE FOAM EDUCTOR MANUAL \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE](#)

[Z GERMAN INLINE ZUMISCHER SERIE 125](#)

[Z PORTUGUESE EDUCTOR MANUAL EDUTOR DE ESPUMA \(PDF\)](#)

[Z SPANISH EDUCTOR SERIE 125 EN LINEA \(PDF\)](#)

Technical Specifications and Drawings

[350 SERIES EDUCTOR EXPLODED VIEW \(PDF\)](#)

[UE-125-NJ-NF ITEM SPECIFICATION \(DOC\)](#)

Technical Bulletins & Testing Reports

[PRODUCT BULLETIN MATERIAL CHANGE UE940 2.5" IN-LINE EDUCTOR](#)

[FOAM PICK-UP HOSE \(PDF\)](#)

ABOUT THE EDUCTOR SERIES

In line foam eductors have a metering head with an easy-to-read knob for use with Class A, B and AR-AFFF foam at a variety of percentages. The meter head is equipped with a unique back flush push-button for fast and easy cleaning right on the scene, and is secured to the eductor body with a rugged disconnect. All controls are easy to use with gloves. The eductors are made of hardcoat anodized aluminum for corrosion protection.

- 125 Eductor Series are available in 60, 95, or 125 gpm models and have foam percentage settings of .25%, .5%, 1%, 3%, & 6% allowing use with Class A or B foams. Models allow you choose between an extra-large 36" pickup hose with stainless steel wand or direct truck connect pickup hose.
- 250 and 350 Eductor Series are 250 gpm and 350 gpm in line Foam eductors for use with Class A foam or Class B foam. A large 8' industrial grade, UV resistant pickup hose is ideal for use with high viscosity foams.