



EDUCTOR Series

**EDUCTOR 250GPM 75MM
STORZ X 75MM STORZ**

UE-250-SL-SL

W/8

\$1750.00 List Price

FEATURES

SPECIFICATIONS

Flow Rate	250gpm (950 l/min)
Inlet	75mm
Inlet Coupling Swivel	Full Time Swivel
Outlet	75mm
Outlet Coupling Swivel	Rigid
Pressure	200psi (14bar)
Weight	15.45

DOCUMENTS

Instructions For Installation, Safe Operation and Maintenance

[EDUCTOR - 350 SERIES: IN-LINE FOAM EDUCTOR \(PDF\)](#)

[EDUCTOR, IN-LINE FOAM EDUCTOR MANUAL \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE \(PDF\)](#)

[Z FRENCH MANUEL : EDUCTOR SÉRIE 125 EN LIGNE](#)

[Z GERMAN INLINE ZUMISCHER SERIE 125](#)

[Z PORTUGUESE EDUCTOR MANUAL EDUTOR DE ESPUMA \(PDF\)](#)

[Z SPANISH EDUCTOR SERIE 125 EN LINEA \(PDF\)](#)

Technical Specifications and Drawings

[350 SERIES EDUCTOR EXPLODED VIEW \(PDF\)](#)

[UE-250-SL-SL ITEM SPECIFICATION \(DOC\)](#)

Technical Bulletins & Testing Reports

[PRODUCT BULLETIN MATERIAL CHANGE UE940 2.5" IN-LINE EDUCTOR](#)

[FOAM PICK-UP HOSE \(PDF\)](#)

ABOUT THE EDUCTOR SERIES

In line foam eductors have a metering head with an easy-to-read knob for use with Class A, B and AR-AFFF foam at a variety of percentages. The meter head is equipped with a unique back flush push-button for fast and easy cleaning right on the scene, and is secured to the eductor body with a rugged disconnect. All controls are easy to use with gloves. The eductors are made of hardcoat anodized aluminum for corrosion protection.

- 125 Eductor Series are available in 60, 95, or 125 gpm models and have foam percentage settings of .25 %, .5 %, 1 %, 3 %, & 6 % allowing use with Class A or B foams. Models allow you choose between an extra-large 36" pickup hose with stainless steel wand or direct truck connect pickup hose.
- 250 and 350 Eductor Series are 250 gpm and 350 gpm in line Foam eductors for use with Class A foam or Class B foam. A large 8' industrial grade, UV resistant pickup hose is ideal for use with high viscosity foams.