



CROSSFIRE Series

SAFE-TAK COMBINATION PACKAGE

XFC-32

CROSSFIRE-BASE-MSTR

\$5310.00 List Price

FEATURES

Rated to 1250 gpm(4500 l/min), the Crossfire® is a portable ground monitor and/or deck mounted monitor. The Crossfire® monitor top with hand wheel provides elevation control from 90° to the safety stop at 30° above horizontal, and is capable of lower elevation angle when truck mounted. The STOW-AWAY portable ground base is available with twin 2-½" (65 mm) clappered inlet, or single large diameter inlet. Optional pressure relief valve and slow close valve (single inlet models only). Includes your choice of a 1,000 or 1,250 gpm (4,000 or 4,500 l/min) Masterstream nozzle. "-NB" at the end of the part number designates Mounting Bracket is NOT included



SPECIFICATIONS

Oscillation	No
Package	Yes
Safety Shutoff	No
Weight	52.2
Safety Inlet	No

DOCUMENTS

Service Procedures

CROSSFIRE XF500-KIT & XP500-KIT INSTALLATION INSTRUCTIONS (PDF)

Instructions For Installation, Safe Operation and Maintenance

CROSSFIRE STORAGE BRACKET (PDF)

CROSSFIRE® MONITOR MANUAL (PDF)

MONITOR EXTENSION PIPE (PDF)

Z FRENCH MANUEL: CANON À EAU CROSSFIRE®

Z GERMAN CROSSFIRE® MONITOR MANUAL (PDF)

Z ITALIAN CROSSFIRE® MONITOR MANUAL (PDF)

Z POLISH CROSSFIRE® MONITOR MANUAL

Z SPANISH MONITOR CROSSFIRE (PDF)

Technical Specifications and Drawings

MONITOR DRAWING AND PART LIST (PDF)

PARTS LIST: CROSSFIRE BRACKET (PDF)

XFC-32 FINISHED GOOD PRINT (PDF)

XFC-32 FINISHED GOOD PRINT (ZIP)

XFC-32 ITEM SPECIFICATION (DOC)

Online Videos

CROSSFIRE CUP SEAL REPLACEMENT (MP4)

CROSSFIRE SERIES VIDEO (MP4)

HOW TO UPGRADE A STANDARD BLITZFIRE TO AN OSCILLATING BLITZFIRE (MP4)

Technical Bulletins & Testing Reports

CROSSFIRE® AND HURRICANE™ SHAFT SEAL CHANGE (PDF)

PRODUCT BULLETIN 3" AND 4" MONITOR FLANGE CONNECTION CHANGE (PDF)

PRODUCT BULLETIN MANUAL EXTEND-A-GUN WITH CROSSFIRE® INLET MOUNT (PDF)

PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE (PDF)

Certifications & Approvals

CROSSFIRE WITH STOW-A-WAY BASE EN15767-1 (PDF)

ABOUT THE CROSSFIRE SERIES

The CROSSFIRE monitor is a unique master stream appliance that's lightweight, compact and incredibly versatile. It can be connected to either a portable base or a truck.

With a flow rating of 1250 gpm in portable operation, the TFT Crossfire monitor integrates the exclusive Safe-Tak safety shutoff system to prevent unintentional movement. The monitor's compact and lightweight design includes stainless spring steel legs with carbide tips for maximum stability, and a visual attachment indicator for additional security.

Connect to a truck with the adapters or a TFT Extend-A-Gun with XL outlet. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 I/min) with low friction loss.