



**CROSSFIRE Series**

**SAFE-TAK COMBINATION PACKAGE**

**XFC-42**

CROSSFIRE-BASE-STACK TIPS-STRAIGHTENER

**\$5065.00 List Price**

**FEATURES**

Rated to 1250 gpm(4500 l/min), the Crossfire® is a portable ground monitor and/or deck mounted monitor. The Crossfire® monitor top with hand wheel provides elevation control from 90° to the safety stop at 30° above horizontal, and is capable of lower elevation angle when truck mounted. The STOW-AWAY portable ground base is available with twin 2-½" (65 mm) clappered inlet, or single large diameter inlet. Optional pressure relief valve and slow close valve (single inlet models only). Includes a set of quad stacked tips and stream straightener. "-NB" at the end of the part number designates Mounting Bracket is NOT included

## SPECIFICATIONS

<b>Oscillation</b>	No
<b>Package</b>	Yes
<b>Safety Shutoff</b>	No
<b>Weight</b>	48.4
<b>Safety Inlet</b>	No

## DOCUMENTS

### Service Procedures

[CROSSFIRE XF500-KIT & XP500-KIT INSTALLATION INSTRUCTIONS \(PDF\)](#)

### Instructions For Installation, Safe Operation and Maintenance

[CROSSFIRE STORAGE BRACKET \(PDF\)](#)

[CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[MONITOR EXTENSION PIPE \(PDF\)](#)

[Z FRENCH MANUEL : CANON À EAU CROSSFIRE®](#)

[Z GERMAN CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[Z ITALIAN CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[Z POLISH CROSSFIRE® MONITOR MANUAL](#)

[Z SPANISH MONITOR CROSSFIRE \(PDF\)](#)

### Technical Specifications and Drawings

[MONITOR DRAWING AND PART LIST \(PDF\)](#)

[PARTS LIST: CROSSFIRE BRACKET \(PDF\)](#)

[XFC-42 FINISHED GOOD PRINT \(PDF\)](#)

[XFC-42 FINISHED GOOD PRINT - STEP \(ZIP\)](#)

[XFC-42 ITEM SPECIFICATION \(DOC\)](#)

### Product Order Forms

[CROSSFIRE COMBINATION PACKAGES ORDER FORM \(PDF\)](#)

### Online Videos

[CROSSFIRE CUP SEAL REPLACEMENT \(MP4\)](#)

[CROSSFIRE SERIES VIDEO \(MP4\)](#)

[HOW TO UPGRADE A STANDARD BLITZFIRE TO AN OSCILLATING BLITZFIRE \(MP4\)](#)

### Technical Bulletins & Testing Reports

[CROSSFIRE® AND HURRICANE™ SHAFT SEAL CHANGE \(PDF\)](#)

[PRODUCT BULLETIN 3" AND 4" MONITOR FLANGE CONNECTION CHANGE \(PDF\)](#)

[PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE \(PDF\)](#)

### Certifications & Approvals

[CROSSFIRE WITH STOW-A-WAY BASE EN15767-1 \(PDF\)](#)

## ABOUT THE CROSSFIRE SERIES

The CROSSFIRE monitor is a unique master stream appliance that's lightweight, compact and incredibly versatile. It can be connected to either a portable base or a truck.

With a flow rating of 1250 gpm in portable operation, the TFT Crossfire monitor integrates the exclusive Safe-Tak safety shutoff system to prevent unintentional movement. The monitor's compact and lightweight design includes stainless spring steel legs with carbide tips for maximum stability, and a visual attachment indicator for additional security.

Connect to a truck with the adapters or a TFT Extend-A-Gun with XL outlet. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 l/min) with low friction loss.