



*REPRESENTATIVE PHOTO

CROSSFIRE Series

SAFE-TAK BASE-5.0"STORZ

XFH-1ST

SINGLE INLET-1250 GPM VERSION

\$2867.00 List Price

FEATURES

is supplied with either two clappered swivel inlets or with a single full-time swivel inlet. The stainless steel, carbide-tipped base support legs can be folded to easily fit inside a small apparatus compartment, or for carrying pre connected to a hose line. Includes a safety tie-down strap with attached storage cap.

SPECIFICATIONS

Coupling Size Side A	5" (125 mm)
Coupling Size Side B	2.5" (65 mm)
Finish	Fire Engine Red
Horizontal Control	N/A
Horizontal Movementdegrees	N/A
Inlet	5" Storz
Max Flow	1,250 gpm (4,500 l/min)
Operation Energy Source	Manual
Oscillation	No
Outlet	Quick Connect Male
Package	No
Safety Shutoff	Yes
Valve Design	No Valve
Vertical Control	N/A
Vertical Movementdegrees	N/A
Weight	30.2
Safety Inlet	No

DOCUMENTS

Service Procedures

[CROSSFIRE XF500-KIT & XP500-KIT INSTALLATION INSTRUCTIONS \(PDF\)](#)

[PARTS LIST: CROSSFIRE & SAFE-TAK 1250 \(PDF\)](#)

[PARTS LIST: CROSSFIRE & SAFE-TAK 1250 \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[CROSSFIRE STORAGE BRACKET \(PDF\)](#)

[CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[MONITOR EXTENSION PIPE \(PDF\)](#)

[Z FRENCH MANUEL : CANON À EAU CROSSFIRE®](#)

[Z GERMAN CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[Z ITALIAN CROSSFIRE® MONITOR MANUAL \(PDF\)](#)

[Z POLISH CROSSFIRE® MONITOR MANUAL](#)

[Z SPANISH MONITOR CROSSFIRE \(PDF\)](#)

Technical Specifications and Drawings

[MONITOR DRAWING AND PART LIST \(PDF\)](#)

[PARTS LIST: CROSSFIRE BRACKET \(PDF\)](#)

[XFH-1ST FINISHED GOOD PRINT \(ZIP\)](#)

[XFH-1ST ITEM SPECIFICATION \(DOC\)](#)

Online Videos

[CROSSFIRE CUP SEAL REPLACEMENT \(MP4\)](#)

[CROSSFIRE SERIES VIDEO \(MP4\)](#)

[HOW TO UPGRADE A STANDARD BLITZFIRE TO AN OSCILLATING BLITZFIRE \(MP4\)](#)

Technical Bulletins & Testing Reports

[CROSSFIRE® AND HURRICANE™ SHAFT SEAL CHANGE \(PDF\)](#)

[PRODUCT BULLETIN 3" AND 4" MONITOR FLANGE CONNECTION CHANGE \(PDF\)](#)

[PRODUCT BULLETIN MANUAL EXTEND-A-GUN WITH CROSSFIRE® INLET MOUNT \(PDF\)](#)

[PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE \(PDF\)](#)

Certifications & Approvals

[CROSSFIRE WITH STOW-A-WAY BASE EN15767-1 \(PDF\)](#)

ABOUT THE CROSSFIRE SERIES

The CROSSFIRE monitor is a unique master stream appliance that's lightweight, compact and incredibly versatile. It can be connected to either a portable base or a truck.

With a flow rating of 1250 gpm in portable operation, the TFT Crossfire monitor integrates the exclusive Safe-Tak safety shutoff system to prevent unintentional movement. The monitor's compact and lightweight design includes stainless spring steel legs with carbide tips for maximum stability, and a visual attachment indicator for additional security.

Connect to a truck with the adapters or a TFT Extend-A-Gun with XL outlet. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 l/min) with low friction loss.

