



CROSSFIRE Series

SAFE-TAK BASE 4.0"STORZ RAL 3000

XPH-1SP

SINGLE INLET-5000 LPM EN VERSION

\$2630.00 List Price

FEATURES

is supplied with either two clappered swivel inlets or with a single full-time swivel inlet. The stainless steel, carbide-tipped base support legs can be folded to easily fit inside a small apparatus compartment, or for carrying pre connected to a hose line. Includes a safety tie-down strap with attached storage cap.



SPECIFICATIONS

Coupling Size Side A	4" (100mm)
Coupling Size Side B	2.5" (65 mm)
Finish	International Red
Horizontal Control	N/A
Horizontal Movementdegrees	N/A
Inlet	4"Storz
Operation Energy Source	Manual
Oscillation	No
Outlet	Quick Connect Male
Package	No
Safety Shutoff	Yes
Valve Design	No Valve
Vertical Control	N/A
Vertical Movementdegrees	N/A
Weight	0
Safety Inlet	No

DOCUMENTS

Service Procedures

CROSSFIRE XF500-KIT & XP500-KIT INSTALLATION INSTRUCTIONS (PDF)

PARTS LIST: CROSSFIRE & SAFE-TAK 1250 (PDF)

PARTS LIST: CROSSFIRE & SAFE-TAK 1250 (PDF)

Instructions For Installation, Safe Operation and Maintenance

CROSSFIRE STORAGE BRACKET (PDF)

CROSSFIRE® MONITOR MANUAL (PDF)

MONITOR EXTENSION PIPE (PDF)

Z FRENCH MANUEL: CANON À EAU CROSSFIRE®

Z GERMAN CROSSFIRE® MONITOR MANUAL (PDF)

Z ITALIAN CROSSFIRE® MONITOR MANUAL (PDF)

Z POLISH CROSSFIRE® MONITOR MANUAL

Z SPANISH MONITOR CROSSFIRE (PDF)

Product Order Forms

CROSSFIRE COMBINATION PACKAGES ORDER FORM (PDF)

Online Videos

CROSSFIRE CUP SEAL REPLACEMENT (MP4)

CROSSFIRE SERIES VIDEO (MP4)

HOW TO UPGRADE A STANDARD BLITZFIRE TO AN OSCILLATING BLITZFIRE (MP4)

Technical Specifications and Drawings

MONITOR DRAWING AND PART LIST (PDF)

PARTS LIST: CROSSFIRE BRACKET (PDF)

Technical Bulletins & Testing Reports

CROSSFIRE® AND HURRICANE™ SHAFT SEAL CHANGE (PDF)

PRODUCT BULLETIN 3" AND 4" MONITOR FLANGE CONNECTION CHANGE

PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL

CHANGE (PDF)

Certifications & Approvals

CROSSFIRE WITH STOW-A-WAY BASE EN15767-1 (PDF)

ABOUT THE CROSSFIRE SERIES

The CROSSFIRE monitor is a unique master stream appliance that's lightweight, compact and incredibly versatile. It can be connected to either a portable base or a truck.

With a flow rating of 1250 gpm in portable operation, the TFT Crossfire monitor integrates the exclusive Safe-Tak safety shutoff system to prevent unintentional movement. The monitor's compact and lightweight design includes stainless spring steel legs with carbide tips for maximum stability, and a visual attachment indicator for additional security.

Connect to a truck with the adapters or a TFT Extend-A-Gun with XL outlet. The connection is easy, positive, and visually verified. When in use, the release is "locked out" by water pressure. The waterway is a large 3.25" (83mm) which lets the CROSSFIRE deliver up to 1250 gpm (4500 I/min) with low friction loss.