



**BLITZTAC Series**

**BLITZTAC 2.5\"/>**

**XXB111A**

**500 GPM PORTABLE MONITOR**

**\$3597.00 List Price**

**FEATURES**

---

**DOCUMENTS**

Technical Specifications and Drawings

[XXB111A ITEM SPECIFICATION \(DOC\)](#)

Certifications & Approvals

[BLITZTAC EN 15767-1 \(PDF\)](#)

[BLITZTAC NFPA 1964 \(PDF\)](#)

Instructions For Installation, Safe Operation and Maintenance

[BLITZTAC PORTABLE MONITOR \(PDF\)](#)

[BLITZTAC STORAGE BRACKET \(PDF\)](#)

Product Brochures

[BLITZTAC PRODUCT SERIES \(PDF\)](#)

Online Videos

[BLITZTAC—ALL NEW TFT PORTABLE MONITOR VIDEO \(MP4\)](#)

Technical Bulletins & Testing Reports

[PRODUCT BULLETIN PORTABLE MONITOR STORAGE BRACKET LABEL CHANGE \(PDF\)](#)

## SPECIFICATIONS

|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>Finish</b>                     | Dark Blue                   |
| <b>Horizontal Control</b>         | N/A                         |
| <b>Horizontal Movementdegrees</b> | 20 left and right of center |
| <b>Inlet</b>                      | 2.5" (65 mm)                |
| <b>Max Flow</b>                   | 500 gpm (2,000 l/min)       |
| <b>Operation Energy Source</b>    | Manual                      |
| <b>Oscillation</b>                | No                          |
| <b>Outlet</b>                     | 2.5" (65 mm)                |
| <b>Package</b>                    | No                          |
| <b>Safety Shutoff</b>             | No                          |
| <b>Valve Design</b>               | Ball Valve (Delrin/Acetal)  |
| <b>Vertical Control</b>           | N/A                         |
| <b>Weight</b>                     | 20.5                        |
| <b>Inlet Connection Type</b>      | NH Female                   |
| <b>Inlet Coupling Style</b>       | Rocker                      |
| <b>Inlet Coupling Swivel</b>      | Full-Time Swivel            |
| <b>Outlet Connection Type</b>     | NH Male                     |
| <b>Outlet Coupling Style</b>      | Male Threads                |
| <b>Outlet Coupling Swivel</b>     | Rigid                       |
| <b>Safety Inlet</b>               | Yes                         |
| <b>Vertical Movement Manned</b>   | 10 to 50 Above Horizontal   |
| <b>Vertical Movement Unmanned</b> | 25 to 50 Above Horizontal   |

## ABOUT THE BLITZTAC SERIES

The Blitztac is one of Task Force Tips' innovative, lightweight, and highly versatile portable attack monitors. Rated up to 500 gpm (2000 l/min), Blitztac integrates a low loss waterway with positive locking valve control, and a corrosion resistant anodized and powder coat finish, while providing a simple easy to reset safety gating device. If the Blitztac starts to slide or lift, the safety gating inlet will automatically reduce the flow of water. To reset, simply close the valve to stop water flow and position the monitor back into the full flow position. The discharge pivots make directing the stream extremely quick and effortless. With an integral stream shaper for superior reach and penetration performance, the Blitztac delivers a 20 degrees side to side range (40 degrees total) and an elevation range of 25 degrees to 50 degrees in unmanned mode, or a low 10 degree angle when manned. The low elevation angle makes it suitable for use indoors. An angled inlet on the hose inlet provides a smooth transition from the hose to the monitor for increased stability. Folding legs have replaceable carbide tipped spikes. An anchor strap with storage bag is included for safe operation.