



### EF1 Series

## EF1 RC 1.5\"/>

Y1-E22A

SWIVEL ROCKER X RIGID MALE

**\$5050.00 List Price**

### FEATURES

The EF1 remotely controlled monitor is compact with a large, efficient waterway capable of flowing up to 200 gpm (757 l/min). Perfect for wildland apparatus or interface apparatus around the globe. At less than 13\"/>

### SPECIFICATIONS

<b>Apparatus</b>	Pumper
<b>Coupling Style Side B</b>	Male Threads
<b>Finish</b>	Stardust Silver
<b>Horizontal Control</b>	N/A
<b>Horizontal Movementdegrees</b>	270 total range
<b>Inlet</b>	1.5\"/>
<b>Max Flow</b>	200 gpm (757 l/min)
<b>Operation Energy Source</b>	12/24 VDC
<b>Oscillation</b>	No
<b>Outlet</b>	1.5\"/>
<b>Remote Control</b>	Yes
<b>Valve Design</b>	No Valve
<b>Vertical Control</b>	N/A
<b>Vertical Movementdegrees</b>	-45 to 90
<b>Weight</b>	17.3

### DOCUMENTS

Technical Specifications and Drawings

[EF1 EXPLODED VIEW \(PDF\)](#)

[Y1-E22A ITEM SPECIFICATION \(DOC\)](#)

[YE-LK12-KIT ITEM SPECIFICATION \(DOC\)](#)

Instructions For Installation, Safe Operation and Maintenance

[EF1 RC MONITOR \(PDF\)](#)

[REMOTE CONTROL \(RC\) MONITOR ELECTRICAL CONTROLS MANUAL \(PDF\)](#)

Product Brochures

[EF1 RC PRODUCT BROCHURE \(PDF\)](#)

Online Videos

[EF1 SERIES VIDEO \(MP4\)](#)

### ABOUT THE EF1 SERIES

The EF1 remotely controlled monitor is a great option for wildland and interface apparatus. At less than 13\"/>

The EF1 is TFT's most compact monitor but its large, efficient waterway is capable of flows up to 200 gpm (760 l/min).